

WEST 1/4 CORNER SECTION 31, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 83 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE WEST 1/4 CORNER OF SECTION 31-20-13 ON THE WEST TOWNSHIP BOUNDARY ON DECEMBER 21, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 19" X 10" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-20-13
- 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 35" X 8" X 3" LIMESTONE THEY SET ON LEVEL GROUND FOR THE CORNER TO TOWNSHIP 20 SOUTH, RANGES 12 & 13 EAST ON THE 4TH STANDARD PARALLEL AT THE SOUTHWEST CORNER OF SECTION 31-20-13

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 18, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 18 DATED MARCH 1-5, 1870 FOR A SURVEY IN SECTION 31-20-13, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 31-20-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING DISTANCES:

- 1) 1,330' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SW1/4 OF SECTION 31-20-13
- 2) 2,660' EAST TO THE LARGE ROCK HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 31-20-13
- 3) 4,020' EAST TO THE STONE HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 31-20-13
- 4) 5,310' EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 31-20-13

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 149 TO 150 [PACKET 317 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] ON THE PETITION OF J. M. McKEE AND OTHERS FOR A ROAD IN TOWNSHIP 21-13 AND TOWNSHIPS 20-12 & 20-13 THAT HE SURVEYED ON APRIL 19, 1870 THAT WAS RECORDED AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS ON MAY 21, 1870 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SHOWS THAT THE SECOND ROAD ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD INTERSECTED THE RANGE LINE AT THE 1/4 CORNER BETWEEN SECTIONS 36-20-12 AND 31-20-13.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS SECOND ROAD EXTENDS WEST ON THE 1/2 SECTION LINE TO THE CENTER CORNER OF SECTION 36-20-12 TO BEGIN THE SECOND ROAD ON THIS ROAD SURVEY
- 2) THIS SECOND ROAD EXTENDS EAST ON THE 1/2 SECTION LINE TO THE CENTER CORNER OF SECTION 32-20-13 AT A TURN TO THE NORTH

- 4) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 68 OF THE 7TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 216 DATED OCTOBER 3, 1872 TO ESTABLISH THE CENTER CORNER OF SECTION 36-20-12 AND SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 32 INTO QUARTERS, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 36-20-12 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,323-1/2' WEST TO THE POST HE SET FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 36-20-12

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,647' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 36-20-12
 - 3) 1,321-1/2' SOUTH TO THE POST HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE SE1/4 OF SECTION 36-20-12 ON THE RANGE LINE
 - 4) 2,643' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 31-20-12 ON THE RANGE LINE AND THE 4TH STANDARD PARALLEL
- 5) LLOYD J. DOBLER, L.S. 541, IN SURVEY F31001 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR A SURVEY FOR A 6.67 ACRE TRACT IN THE SOUTHWEST QUARTER OF SECTION 31-20-13 FOR CRAIG WOLFORD DATED MAY 15, 1978, SHOWS ON HIS SURVEY DRAWING A "MONUMENT" AT THE NORTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 31-20-13 ON THE RANGE LINE. **NOTE: VERIFY BEFORE USING AS THERE IS NO DESCRIPTION OF THE MONUMENT AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,634.42' SOUTH ON THE RANGE LINE TO THE "MONUMENT" AT THE SOUTHWEST CORNER OF SECTION 31-20-13 ON THE 4TH STANDARD PARALLEL
 - 2) 453.57' EAST TO THE 3/4" IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE 6.67 ACRE TRACT
 - 3) 744.07' EAST TO THE 3/4" IRON PIN HE SET FOR THE NORTHEAST CORNER OF THE 6.67 ACRE TRACT
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 15, 1999, FOR JOB NUMBER 99256-02, SAID THAT **HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/4 CORNER OF SECTION 31-20-13 ACCORDING TO THE FAS BRIDGE PLANS ON FILE IN THE COUNTY ENGINEER'S OFFICE.
- 1) 32.0' NNW TO A 40 D SPIKE & WASHER IN A WOOD POST
 - 2) 34.8' NNE TO A 40 D SPIKE & WASHER IN A WOOD POST
 - 3) 40.0' SOUTH TO A LINE OF FENCE EAST-WEST
 - 4) IN LINE WITH A FENCE TO THE SOUTH EXTENDED
 - 5) 1.0' SOUTH TO THE CENTER OF THE TRAVELED WAY EAST-WEST

WEST QUARTER CORNER 31-20-13