

NORTH 1/4 CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 678 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 29 & 32-20-13.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.05-1/2 CHAINS WEST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 29, 30, 31 & 32-20-13
 - 2) 40.05-1/2 CHAINS EAST TO THE 22" X 8" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 28, 29, 32 & 33-20-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 19, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 19 DATED MARCH 1-5, 1870 TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 32-20-13, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 32-20-13 ON THIS **PERMANENT SURVEY**.
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 149 TO 150 [PACKET 317 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE] ON THE PETITION OF J. M. McKEE AND OTHERS FOR A ROAD IN TOWNSHIP 21-13 AND TOWNSHIPS 20-12 & 20-13 THAT HE SURVEYED ON APRIL 19, 1870 THAT WAS RECORDED AND ORDERED BY THE BOARD OF COUNTY COMMISSIONERS ON MAY 21, 1870 AS NOTED BY DAVID S. GILMORE, COUNTY CLERK, SHOWS ON HIS SURVEY DRAWING THE SECOND ROAD ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD HAS A TURN AT THE NORTH 1/4 CORNER OF SECTION 32-20-13.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS SECOND ROAD EXTENDS SOUTH ON THE 1/2 SECTION LINE TO THE CENTER CORNER OF SECTION 32-20-13 AT A TURN TO THE WEST
 - 2) THIS SECOND ROAD EXTENDS EAST ON THE SECTION LINE TO THE NORTH-WEST CORNER OF SECTION 33-20-13 AT A TURN TO THE NORTHEASTERLY TO THE NORTHWEST CORNER OF SECTION 22-20-13
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 21, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 202 DATED FEBRUARY 25-28, 1901 ORDERED BY J. L. PORTER TO ESTABLISH THE NORTHEAST AND SOUTHEAST CORNERS OF SECTION 33-20-13, APPARENTLY DID **NOT** FIND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 32-20-13 AS HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 31-20-13 EAST TO THE GOVERNMENT STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-20-13 ON THE RANGE LINE ON THIS **PERMANENT SURVEY**.
- 5) FINNEY & TURNIPSEED PLANS FOR BRIDGE NUMBER 965.5-536.9 SHOWS A **1/2" REBAR AT "THE INTERSECTION"** AT P.O.T. STATION 536+49.50 FOR THE NORTH 1/4 CORNER OF SECTION 32-20-13. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS REBAR MAY HAVE BEEN "HEELED-IN" FOR THE BRIDGE SURVEY!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 26.35' NORTH TO A SPIKE IN THE TOP OF A CORNER FENCE POST
 - 2) 45.50' NW TO A SPIKE IN A TELEPHONE POLE
 - 3) 47.95' SW TO A SPIKE IN A POWER POLE
- 6) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 2008 FOR PROJECT NUMBER 08300-02, SURVEY F29001 IN THE SURVEY FILE FOR TOWNSHIP 20-13 FOR THE SURVEY OF A 7.43 ACRE TRACT IN THE NORTH HALF OF THE SOUTHEAST QUARTER AND A

PREVIOUSLY DESCRIBED TRACT IN THE SOUTH HALF OF THE SOUTHEAST QUARTER OF SECTION 29-20-13 FOR DENNY DARBYSHIRE, SAID THAT HE CONSIDERED THAT THE SOUTH 1/4 CORNER OF SECTION 29-20-13 WAS **OBLITERATED**. HE SET A 5/8" REBAR WITH A LYON COUNTY CAP FOR THE SOUTH 1/4 CORNER OF SECTION 29-20-13 ON TRUE LINE BETWEEN THE SOUTHEAST AND SOUTHWEST CORNERS OF SECTION 29-20-13, AND 25 FEET EAST OF THE HEDGE ON THE WEST SIDE OF THE COUNTY ROAD GOING SOUTH THROUGH THE CENTER OF SECTION 32-20-13.

- 1) 13' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 80 EAST-WEST
- 2) 30' WEST TO A FENCE TO THE NORTH
- 3) 8' WEST TO THE CENTERLINE TRAVELED WAY OF THE ROAD TO THE SOUTH
- 4) 31.1' ENE TO THE TOP CENTER OF THE NORTH HUBGUARD
- 5) 58.15' ESE TO THE TOP CENTER OF THE SOUTH HUBGUARD

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,663.07' WEST TO THE MAG NAIL IN ASPHALT HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 29-20-13
- 2) 2,587.20' EAST TO THE MAG NAIL IN ASPHALT HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 29-20-13
- 3) 1,326.22' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF SECTION 29-20-13
- 4) 2,652.44' NORTH TO THE THEORETICAL LOCATION FOR THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 29-20-13
- 5) 5,314.99' NORTH TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 29-20-13

NORTH QUARTER CORNER 32-20-13