

SOUTH 1/4 CORNER SECTION 32, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 23 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE ROCK 25" X 8" X 4-1/2"** ON LEVEL GROUND FOR THE SOUTH 1/4 CORNER OF SECTION 32-20-13 ON THE 4TH STANDARD PARALLEL ON NOVEMBER 21, 1855.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 4TH STANDARD PARALLEL TO THE 31" X 6" X 5" LIMESTONE THEY SET IN THE BOTTOM FOR THE CORNER TO SEC. 31 & 32-20-13
 - 2) 40.00 CHAINS EAST ON THE 4TH STANDARD PARALLEL TO THE 31" X 5" X 4" LIMESTONE THEY SET ON LEVEL GROUND FOR THE CORNER TO SECTIONS 32 & 33-20-13
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 17, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 17 DATED MARCH 1-5, 1870 FOR A SURVEY IN THE NORTHWEST 1/4 OF SECTION 5-21-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 32-20-13 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 2,414' WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-21-13

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 19, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 19 DATED MARCH 1-5, 1870 TO SUBDIVIDE THE SOUTHEAST 1/4 OF SECTION 32-20-13, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF 32-20-13 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 1,327-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SE1/4 OF SECTION 32-20-13
- 2) 2,655' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 32-20-13
- 3) 1,322-1/2' EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT SOUTH 1/2/4 CORNER OF THE SE1/4 OF SECTION 32-20-13
- 4) 1,982-1/2' EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE SET FOR THE CORNER OF A 20 ACRE LOT ON THE WEST SIDE OF THE SE1/4 OF THE SE1/4 OF SECTION 32-20-13
- 5) 2,645' EAST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 32-20-13

- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 21, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 202 DATED FEBRUARY 25-28, 1901 ORDERED BY J. L. PORTER TO ESTABLISH THE NORTHEAST AND SOUTHEAST CORNERS OF SECTION 33-20-13, APPARENTLY DID **NOT** FIND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 32-20-13 AS HE RAN THE 4TH STANDARD PARALLEL FROM THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 32-20-13 EAST TO THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF SECTION 33-20-13 ON THIS **PERMANENT SURVEY** AND DID NOT MENTION THE SOUTH 1/4 CORNER OF SECTION 32-20-13.

SOUTH QUARTER CORNER 32-20-13