

EAST 1/4 CORNER SECTION 34, TOWNSHIP 20 SOUTH, RANGE 13 EAST

- 1) ON PAGE 667 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 34 & 35-20-13 ON THE COUNTY LINE ON JANUARY 10, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE COUNTY LINE TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 34 & 35-20-13
 - 2) 40.00 CHAINS SOUTH ON THE COUNTY LINE TO THE 33" X 9" X 3" LIMESTONE THEY SET ON A SLOPE TO THE WEST FOR THE CORNER TO SECTIONS 34 & 35-20-13 ON THE COUNTY LINE
- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 159, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 123 DATED DECEMBER 19, 1906 THAT WAS **ORDERED BY THE DISTRICT COURT OF LYON COUNTY** FOR TWO TRACTS IN THE NORTHWEST 1/4 OF SECTION 34-20-13, WITH ADDITIONAL INFORMATION IN PACKET "M 193" IN MISCELLANEOUS DRAWER NUMBER 8 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 34-20-13 ON THE LYON AND COFFEY COUNTY LINE ON THIS **PERMANENT SURVEY ORDERED BY THE DISTRICT COURT OF LYON COUNTY.**

PACKET "M 193" SHOWS THE FOLLOWING INFORMATION:

- 1) 40.64 CHAINS NORTH ON THE COUNTY LINE TO THE LARGE CORNER POST HE FOUND ON THE SECTION LINE AT THE NORTHEAST CORNER OF SEC. 34-20-13
- 2) 81.28 CHAINS NORTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 27-20-13

- 3) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN SURVEY F34001 IN THE SURVEY FILE FOR TOWNSHIP 20-13, FOR THE PARTIAL BOUNDARY SURVEYS JOHN REDMOND DAM AND RESERVOIR GRAND (NEOSHO) RIVER PERFORMED UNDER CONTRACT NUMBER DACW56-75-C-0219 RECORDED IN FIELD BOOK NUMBER 5-1916 DATED APRIL 1996 AND FILED IN THE REGISTER OF DEEDS OFFICE ON JUNE 29, 1976 IN VOLUME 347 ON PAGE 259, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1" X 2' IRON BAR** FOR THE EAST 1/4 CORNER OF SECTION 34-20-13 ON THE LYON AND COFFEY COUNTY LINE HALFWAY BETWEEN THE STANDARD CORPS OF ENGINEER'S CONCRETE MONUMENT HE SET FOR THE NORTHEAST CORNER OF SECTION 34-20-13 AND THE 1" IRON BAR HE SET FOR THE SOUTHEAST CORNER OF SECTION 34-20-13. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THE SURVEYS FOR JOHN REDMOND WERE POORLY RESEARCHED AND LITTLE, IF ANY, EFFORT WAS MADE TO CHECK FOR THE STONES OF RECORD- WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**

- 1) S. 76°00' E. 19.53' TO A SPIKE & WASHER IN A 40" ELM TREE
- 2) N. 87°00' W. 23.85' TO A SPIKE & WASHER IN A 30" WALNUT TREE
- 3) S. 48°00' E. 50.25' TO A SPIKE & 3 WASHERS IN AN 80" WALNUT TREE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,636.19' SOUTH ON THE COUNTY LINE TO THE 1" IRON BAR HE SET FOR THE SOUTHEAST CORNER OF SECTION 34-20-13
- 2) 1,936.18' NORTH ON THE COUNTY LINE TO THE STANDARD CORPS OF ENGINEERS CONCRETE MONUMENT HE SET
- 3) 2,236.18' NORTH ON THE COUNTY LINE TO THE STANDARD CORNS OF ENGINEER'S MONUMENT HE SET
- 4) 2,636.19' NORTH ON THE COUNTY LINE TO THE STANDARD CORPS OF ENGINEERS CONCRETE MONUMENT SET FOR THE NORTHEAST CORNER OF SECTION 34-20-13

CONTINUED ON PAGE 2

- 4) JOHN R. YOUNG, L.S. 112, OF SCHWAB-EATON, P.A., IN SURVEY F35001 IN THE SURVEY FILE FOR TOWNSHIP 20-13, FOR THE PARTIAL BOUNDARY SURVEYS JOHN REDMOND DAM AND RESERVOIR GRAND (NEOSHO) RIVER PERFORMED UNDER CONTRACT NUMBER DACW56-75-C-0219 RECORDED IN FILED BOOK NUMBER 9-1917 DATED APRIL 1996, SHOWS ON HIS SURVEY DRAWING THAT **HE SET A 1" X 2" IRON BAR** FOR THE WEST 1/4 CORNER OF SECTION 35-20-13 ON THE LYON AND COFFEY COUNTY LINE HALFWAY BETWEEN THE STANDARD CORPS OF ENGINEER'S CONCRETE MONUMENT HE SET FOR THE NORTHWEST CORNER OF SECTION 35-20-13 AND THE 1" IRON BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 35-20-13. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THE SURVEYS FOR JOHN REDMOND WERE POORLY RESEARCHED AND LITTLE, IF ANY, EFFORT WAS MADE TO CHECK FOR THE STONES OF RECORD- WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) S. 76°00' E. 19.53' TO A SPIKE & WASHER IN A 40" ELM TREE
 - 4) N. 87°00' W. 23.85' TO A SPIKE & WASHER IN A 30" WALNUT TREE
 - 5) S. 48°00' E. 50.25' TO A SPIKE & 3 WASHERS IN AN 80" WALNUT TREE
- HIS DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,636.19' SOUTH ON THE COUNTY LINE TO THE 1" IRON BAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 35-20-13
 - 2) 1,936.18' NORTH ON THE COUNTY LINE TO THE STANDARD CORPS OF ENGINEER'S CONCRETE MONUMENT HE SET
 - 5) 2,636.19' NORTH ON THE COUNTY LINE TO THE STANDARD CORPS OF ENGINEER'S CONCRETE MONUMENT HE SET FOR THE NORTHWEST CORNER OF SECTION 35-20-13

EAST QUARTER CORNER 34-20-13