

WEST 1/4 CORNER SECTION 03, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 259 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-21-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 42.41 CHAINS NORTH TO THE 28" X 14" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3 & 4-21-10 ON THE 4TH STANDARD PARALLEL
 - 2) 40.00 CHAINS SOUTH TO THE 22" X 17" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-21-10

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 9, 2012 FOR PROJECT NUMBER 11330-02, SURVEY F03001 IN THE SURVEY FILE FOR TOWNSHIP 21-10, A SURVEY OF THE EAST 120 ACRES OF THE NORTHEAST 1/4 OF SECTION 3-21-10 FOR BRYAN DAVIS, SAID THAT **HE FOUND THE 18" X 14" X 4" LIMESTONE MARKED "1/4" WITH THE TOP BROKEN OFF AT THE WEST 1/4 CORNER OF SECTION 3-21-10. HE SET 1/2" IRON BARS ON THE EAST AND WEST SIDES AT THE CENTER OF THE STONE, AND THE TOP PIECE MARKED "1/4" WAS SET ON THE EAST SIDE OF THE STONE AT THE WEST 1/4 CORNER OF SECTION 3-21-10.**
 - 1) 1/2" IRON BAR W/ "BROSEMER 752" CAP SET ON EAST AND WEST SIDES CENTER OF THE STONE
 - 2) 87.7' SW TO A 16 D NAIL & WASHER IN AN 8" LOCUST TREE
 - 3) 157.6' WEST TO A FENCE LINE NORTH-SOUTHHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,644.55' SOUTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-21-10
 - 2) 2,661.66' EAST TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 3-21-10
 - 3) 3,424.61' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE EAST 120 ACRES OF THE NE1/4 OF SEC. 3-21-10
 - 4) 5,313.79' EAST TO THE 1/2" IRON PIN WITH HIS "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 3-21-10

WEST QUARTER CORNER 03-21-10