

WEST 1/4 CORNER SECTION 12, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 249 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 14" X 12" X 6"** FOR THE 1/4 CORNER BETWEEN SECTIONS 11 & 12-21-10.

- 2) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN AN **INFORMAL SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 151 DATED APRIL 5, 1883 AT THE REQUEST OF BURKHEART TO ESTABLISH THE CENTER CORNER AND THE 1/8TH CORNERS ON THE NORTH & SOUTH LINES OF THE NORTHWEST 1/4 OF SECTION 11-21-10, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 11-21-10 ON THIS **INFORMAL SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 80.61 CHAINS WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 11-21-10

- 3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 20, 1985, FOR JOB NUMBER 85074, SURVEY F02001 IN THE SURVEY FILE FOR TOWNSHIP 21-10 TO SURVEY THE SOUTH HALF OF THE SOUTHWEST QUARTER OF SECTION 2 20-10 AND RECORDED IN VOLUME 417 ON PAGE 299 IN THE REGISTER OF DEEDS OFFICE ON JUNE 27, 1985, SAID THAT HE DID **NOT** DIG FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 11-21-10 ON THIS SURVEY.

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 23, 1989, FOR JOB NUMBER 89061, SAID THAT HE CONSIDERED THAT THE WEST 1/4 CORNER OF SECTION 12-21-10 WAS **LOST**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/4 CORNER OF SECTION 12-21-10.
 - 1) 45.9' NE TO A NAIL & WASHER IN A POWER POLE
 - 2) 29.0' EAST TO A LINE OF POWER POLES
 - 3) 25.95' WEST TO A NAIL & WASHER IN A FENCE POST
 - 4) 26.0' WEST TO A NORTH-SOUTH FENCE LINE
 - 5) 2.0' WEST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD NORTH-SOUTH

WEST QUARTER CORNER 12-21-10