

NORTHWEST CORNER SECTION 19, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 113 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 20" X 2"** FOR THE CORNER TO SECTIONS 18 & 19-21-10 ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE ON MARCH 17, 1857.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 24" X 10" X 2" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 19-21-10
 - 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY AND THE COUNTY LINE TO THE 24" X 6" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-21-10
 - 3) 35.40 CHAINS EAST TO THE 19" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 18 & 19-21-10
 - 4) 75.40 CHAINS EAST TO THE 24" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-21-10
- 2) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 79 DATED DECEMBER 11, 1883 FOR A ROAD IN TOWNSHIP 21, RANGE 10 FOR G. O. HUGHES, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 18-21-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY. HE NOTED THAT THE ROAD IS 50 FEET WIDE EXCEPT FOR THAT PORTION THAT DEVIATES FROM THE SECTION LINE DUE TO SHAW CREEK IN THE NORTHEAST 1/4 OF SECTION 21-20-10.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2-1/2 MILES TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-10; THENCE CONTINUES EAST ON THE SECTION LINES FOR 1,170 FEET TO A ROAD STONE HE SET; THENCE ON AN ANGLE TO THE SOUTHEASTERLY FOLLOWING THE BENDS OF SHAW CREEK FOR 630 FEET [THIS LAST TO BE 40 FEET WIDE FROM THE BANK OF SHAW CREEK, ALL THE BALANCE OF ROAD 50 FEET]; THENCE N. 49°30' E. FOR 120 FEET TO A ROAD STONE HE SET ON THE SECTION LINE; THEN EAST ON THE SECTION LINE FOR 770 FEET TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-21-10; THEN FROM A POINT 44 FEET SOUTH OF THE SECTION LINE ON THE SOUTH SIDE OF THE ROAD AND PARALLEL TO IT FOR 80 RODS ON THE SOUTH SIDE OF A HEDGE; THEN CONTINUES EAST ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 14-21-10 TO THE TERMINUS OF THIS ROAD SURVEY
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 246 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 570 TO 572 PETITION BY G. O. HUGHES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-10 [PACKET 492 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 11, 1883, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, EXCEPT THAT PORTION ALONG SHAW CREEK WHICH WILL BE 40 FEET WIDE ACCORDING TO THE FIELD NOTES, ON JANUARY 14, 1884 BY THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 26, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 18-21-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES FOR 2-1/2 MILES TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-10; THENCE

CONTINUES EAST ON THE SECTION LINES FOR 1,170 FEET TO A ROAD STONE HE SET; THENCE ON AN ANGLE TO THE SOUTHEASTERLY FOLLOWING THE BENDS OF SHAW CREEK FOR 630 FEET [THIS LAST TO BE 40 FEET WIDE FROM THE BANK OF SHAW CREEK, ALL THE BALANCE OF ROAD 50 FEET]; THENCE N. 49°30' E. FOR 120 FEET TO A ROAD STONE HE SET ON THE SECTION LINE; THEN EAST ON THE SECTION LINE FOR 770 FEET TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-21-10; THEN FROM A POINT 44 FEET SOUTH OF THE SECTION LINE ON THE SOUTH SIDE OF THE ROAD AND PARALLEL TO IT FOR 80 RODS ON THE SOUTH SIDE OF A HEDGE; THEN CONTINUES EAST ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 14-21-10 TO THE TERMINUS OF THIS ROAD SURVEY

NORTHWEST CORNER 19-21-10