

**NORTHWEST CORNER SECTION 23, TOWNSHIP 21 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 252 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE CORNER TO SECTIONS 14, 15, 22 & 23-21-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.19-1/2 CHAINS EAST TO THE 16" X 10" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-21-10
- 2) 80.39 CHAINS EAST TO THE 24" X 16" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTION 22, 23, 26 & 27-21-10

- 2) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 79 DATED DECEMBER 11, 1883 FOR A ROAD IN TOWNSHIP 21, RANGE 10 FOR G. O. HUGHES, PRINCIPAL PETITIONER, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 15-21-10 ON THIS ROAD SURVEY. HE NOTED THAT THE ROAD IS 50 FEET WIDE EXCEPT FOR THAT PORTION THAT DEVIATES FROM THE SECTION LINE DUE TO SHAW CREEK IN THE NORTHEAST 1/4 OF SECTION 21-20-10.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO A ROAD STONE HE SET AT 80 RODS EAST OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE SOUTH FOR 44 FEET; THENCE WEST AT 44 FEET SOUTH OF THE SECTION LINE AND PARALLEL TO IT FOR 80 RODS ON THE SOUTH SIDE OF THE HEDGE TO A ROAD STONE HE SET AT 44 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE NORTH FOR 44 FEET TO THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE WEST ON THE SECTION LINES FOR 770 FEET TO A ROAD STONE HE SET; THENCE S. 49°30' W. FOR 120 FEET TO A ROAD STONE HE SET; THENCE ON AN ANGLE TO THE NORTHWESTERLY FOLLOWING THE BENDS OF SHAW CREEK FOR 630 FEET [THIS LAST TO BE 40 FEET WIDE FROM THE BANK OF SHAW CREEK, ALL THE BALANCE OF ROAD 50 FEET] TO A ROAD STONE HE SET ON THE SECTION LINE; THENCE WEST ON THE SECTION LINES FOR 1,170 FEET TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-10; THENCE WEST ON THE SECTION LINES FOR 2-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-21-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 14-21-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 246 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 570 TO 572 PETITION BY G. O. HUGHES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-10 [PACKET 492 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 11, 1883, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, EXCEPT THAT PORTION ALONG SHAW CREEK WHICH WILL BE 40 FEET WIDE ACCORDING TO THE FIELD NOTES, ON JANUARY 14, 1884 BY THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 26, 1884 BY ROLAND LARKIN, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 22-21-10 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO A ROAD STONE HE SET AT 80 RODS EAST OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE SOUTH FOR 44 FEET; THENCE WEST AT 44 FEET SOUTH OF THE SECTION LINE AND PARALLEL TO IT FOR 80 RODS ON THE SOUTH SIDE OF THE HEDGE TO A ROAD STONE HE SET AT 44 FEET SOUTH OF THE NORTHEAST CORNER OF

SECTION 21-21-10; THENCE NORTH FOR 44 FEET TO THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE WEST ON THE SECTION LINES FOR 770 FEET TO A ROAD STONE HE SET; THENCE S. 49°30' W. FOR 120 FEET TO A ROAD STONE HE SET; THENCE ON AN ANGLE TO THE NORTHWESTERLY FOLLOWING THE BENDS OF SHAW CREEK FOR 630 FEET [THIS LAST TO BE 40 FEET WIDE FROM THE BANK OF SHAW CREEK, ALL THE BALANCE OF ROAD 50 FEET] TO A ROAD STONE HE SET ON THE SECTION LINE; THENCE WEST ON THE SECTION LINES FOR 1,170 FEET TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-10; THENCE WEST ON THE SECTION LINES FOR 2-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-21-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY

- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE SOUTHEAST CORNER OF SECTION 14-21-10 TO THE TERMINUS OF THIS ROAD SURVEY
  
- 4) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 50, A ROAD SURVEY FOR A ROAD IN TOWNSHIP 21, RANGE 10 RECORDED IN SURVEY BOOK "E" ON PAGE 50 DATED AUGUST 11, 1884 FOR H. R. MILNER, PRINCIPAL PETITIONER, SAID THAT HE BEGAN THIS ROAD SURVEY AT THE NORTHEAST CORNER OF SECTION 15-21-10 AND RAN SOUTH ON THE SECTION LINE TO THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF THE SOUTHEAST 1/4 OF SECTION 27-21-10, INDICATING THAT HE EITHER FOUND OR SET THE NORTHEAST CORNER OF SECTION 22-21-10 ON THIS ROAD SURVEY.
  
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 65, A ROAD SURVEY IN TOWNSHIP 21-10 FOR W. W. COVERT, PRINCIPAL PETITIONER, RECORDED IN SURVEY BOOK "F" ON PAGE 144 DATED NOVEMBER 25, 1902, SAID THAT **HE FOUND THE STONE LOCATED 20 FEET NORTH AND 8 FEET WEST OF A CORNER FENCE POST** AT THE NORTHWEST CORNER OF SECTION 23-21-10 ON THIS ROAD SURVEY FOR A 40 FOOT WIDE ROAD, BEING 20 FEET EACH SIDE OF THE SECTION LINE.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 80.06 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-21-10 AT THE TERMINUS OF THIS ROAD SURVEY
  - 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 80.06 CHAINS TO THE GOVERNMENT STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 23-21-10 TO BEGIN THIS ROAD SURVEY
  
- 6) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 581 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 193 THROUGH 196 PETITIONED BY W. W. COVERT AND OTHERS FOR A ROAD IN TOWNSHIP 21-10 [PACKET 716 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON NOVEMBER 25, 1902, WAS ESTABLISHED AT 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE, ON FEBRUARY 5, 1903 AS NOTED BY E. MOORHEAD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON FEBRUARY 18, 1903 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE [LOCATED 20 FEET NORTH AND 8 FEET WEST OF A CORNER FENCE POST]** AT THE NORTHWEST CORNER OF SECTION 23-21-10 ON THIS ROAD SURVEY.  
HIS NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 80.06 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 14-21-10 AT THE TERMINUS OF THIS ROAD SURVEY

HIS INFORMATION IS CONTINUED ON PAGE 3

- 2) THIS ROAD EXTENDS SOUTH ON THE SECTION LINES FOR 80.06 CHAINS TO THE GOVERNMENT STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 23-21-10 TO BEGIN THIS ROAD SURVEY
  
- 7) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 6, 1999, FOR PROJECT NUMBER 99208-02, SURVEY F15001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF TWO TRACTS IN THE SOUTHWEST QUARTER OF SECTION 15-21-10, SAID THAT HE EXCAVATED FOR THE STONE AT THE SOUTHEAST CORNER OF SECTION 15-21-10, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE SOUTHEAST CORNER OF SECTION 15-21-10 BASED ON THE PHYSICAL EVIDENCE THAT HE FOUND AT THIS CORNER, AND CONFIRMED BY MEASUREMENT FROM A PERMANENT SURVEY BY ALVA J. SMITH IN 1902 RECORDED IN SURVEY BOOK "F" ON PAGE 144.
  - 1) 32.3' SE TO A CONCRETE NAIL & SHINER IN A POWER POLE
  - 2) 41.0' SE TO A CONCRETE NAIL & SHINER IN A GATE POST
  - 3) 49.8' NW TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 4) 3' SOUTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 40 TO THE WEST
  - 5) IN THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "E" NORTH-SOUTH

NORTHWEST CORNER 23-21-10