

**NORTHWEST CORNER SECTION 24, TOWNSHIP 21 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 247 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 16" X 4"** FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-21-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.16 CHAINS EAST TO THE 14" X 12" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 24-21-10
  - 2) 80.32 CHAINS EAST TO THE 22" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13 & 24-21-10 ON THE EAST TOWNSHIP BOUNDARY
- 2) ARTHUR MILLIKEN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "F", ON PAGE 79 DATED DECEMBER 11, 1883 FOR A ROAD IN TOWNSHIP 21, RANGE 10 FOR G. O. HUGHES, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 14-21-10 TO END THIS ROAD SURVEY. HE NOTED THAT THE ROAD IS 50 FEET WIDE **EXCEPT** FOR THAT PORTION THAT DEVIATES FROM THE SECTION LINE DUE TO SHAW CREEK IN THE NORTHEAST 1/4 OF SECTION 21-20-10.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO A ROAD STONE HE SET AT 80 RODS EAST OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE SOUTH FOR 44 FEET; THENCE WEST AT 44 FEET SOUTH OF THE SECTION LINE AND PARALLEL TO IT FOR 80 RODS ON THE SOUTH SIDE OF THE HEDGE TO A ROAD STONE HE SET AT 44 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE NORTH FOR 44 FEET TO THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE WEST ON THE SECTION LINES FOR 770 FEET TO A ROAD STONE HE SET; THENCE S. 49°30' W. FOR 120 FEET TO A ROAD STONE HE SET; THENCE ON AN ANGLE TO THE NORTHWESTERLY FOLLOWING THE BENDS OF SHAW CREEK FOR 630 FEET [THIS LAST TO BE 40 FEET WIDE FROM THE BANK OF SHAW CREEK, ALL THE BALANCE OF ROAD 50 FEET] TO A ROAD STONE HE SET ON THE SECTION LINE; THENCE WEST ON THE SECTION LINES FOR 1,170 FEET TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-10; THENCE WEST ON THE SECTION LINES FOR 2-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-21-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY FOR ROAD NUMBER 246 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 570 TO 572 PETITION BY G. O. HUGHES AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-10 [PACKET 492 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 11, 1883, AND WAS ESTABLISHED AS A 50 FOOT WIDE ROAD, **EXCEPT** THAT PORTION ALONG SHAW CREEK WHICH WILL BE 40 FEET WIDE ACCORDING TO THE FIELD NOTES, ON JANUARY 14, 1884 BY THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 26, 1884 BY ROLAND LARKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 14-21-10 AT THE TERMINUS OF THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO A ROAD STONE HE SET AT 80 RODS EAST OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE SOUTH FOR 44 FEET; THENCE WEST AT 44 FEET SOUTH OF THE SECTION LINE AND PARALLEL TO IT FOR 80 RODS ON THE SOUTH SIDE OF THE HEDGE TO A ROAD STONE HE SET AT 44 FEET SOUTH OF THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE NORTH FOR 44 FEET TO THE NORTHEAST CORNER OF SECTION 21-21-10; THENCE WEST ON THE SECTION LINES FOR 770 FEET TO A

ROAD STONE HE SET; THENCE S. 49°30' W. FOR 120 FEET TO A ROAD STONE HE SET; THENCE ON AN ANGLE TO THE NORTHWESTERLY FOLLOWING THE BENDS OF SHAW CREEK FOR 630 FEET [THIS LAST TO BE 40 FEET WIDE FROM THE BANK OF SHAW CREEK, ALL THE BALANCE OF ROAD 50 FEET] TO A ROAD STONE HE SET ON THE SECTION LINE; THENCE WEST ON THE SECTION LINES FOR 1,170 FEET TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-10; THENCE WEST ON THE SECTION LINES FOR 2-1/2 MILES TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 18-21-10 ON THE RANGE LINE AND THE LYON AND CHASE COUNTY LINE TO BEGIN THIS ROAD SURVEY

- 4) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 170, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 134 DATED JULY 16-20, 1888 AT THE REQUEST OF L. NEWMAN TO ESTABLISH THE CORNERS OF THE NORTHEAST 1/4 AND THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 35-21-10, SAID THAT **HE FOUND THE STONE IN THE GROUND AND IN GOOD CONDITION** AT THE CORNER TO SECTIONS 13, 14, **25 & 26** ON THIS **PERMANENT SURVEY**. [**NOTE:** THIS IS THE CORNER TO SECTIONS 13, 14, **23 & 24** – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR] HIS NOTES SHOW THE FOLLOWING INFORMATION:
- 1) 2,625' SOUTH TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 23-21-10
  - 2) 10,545.7' SOUTH TO THE OLD GOVERNMENT STONE **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 35-21-10
  - 3) 13,180.92' SOUTH TO THE 17" X 15" X 3" SANDSTONE MARKED "1/4" ON THE WEST SIDE FOR THE PERMANENT EAST 1/4 CORNER OF SECTION 35-21-10
  - 4) 14,326.1' SOUTH TO A LINE TREE PER THE GOVERNMENT NOTES HE FOUND ON THE EAST LINE OF SECTION 35-21-10
  - 5) 15,798' SOUTH TO THE "CORNER SET BY SOME SURVEYOR" THAT HE FOUND BUT HE DID **NOT** USE ON THIS PERMANENT SURVEYOR

NORTHWEST CORNER 24-21-10