

**NORTH 1/4 CORNER SECTION 26, TOWNSHIP 21 SOUTH, RANGE 10 EAST**

- 1) ON PAGE 252 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 23 & 26-21-10.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.07-1/2 CHAINS WEST TO THE 21" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 22, 23, 26 & 27-21-10
- 2) 40.07-1/2 CHAINS EAST TO THE 28" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 23, 24, 25 & 26-21-10

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 161, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 125 DATED DECEMBER 24, 1906, FOR A ROAD IN TOWNSHIP 21, RANGE 10 FOR P. E. LAMOUREUX, SAID THAT **HE FOUND THE STONE IN PLACE ON LINE WITH A FENCE TO THE SOUTH** AT THE NORTH 1/4 CORNER OF SECTION 26-21-10 ON THIS ROAD SURVEY. HE NOTED THAT THIS ROAD IS ON THE SECTION LINE AND 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE, EXCEPTING THAT PORTION BETWEEN THE ROAD STONES FOR THE WIDE PORTION BETWEEN SECTIONS 22 & 27 WHICH IS 65 FEET WIDE, 20 FEET ON THE NORTH SIDE OF THE SECTION LINE AND 45 SOUTH ON THE SOUTH SIDE OF THE SECTION LINE. THE OLD ROAD BETWEEN THE BEGINNING AND THE TERMINUS OF THIS NEW ROAD WAS **VACATED.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT 23 FEET EAST AND 19 FEET SOUTH OF FENCES AT THE NORTHEAST CORNER OF SECTION 26-21-10 TO BEGIN THIS ROAD SURVEY
- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE GOVERNMENT STONE AT 20 FEET WEST AND 20 FEET SOUTH OF A FENCE CORNER AT THE NORTHWEST CORNER OF SECTION 26-21-10; THEN CONTINUES WEST ON THE SECTION LINES FOR 38.25 CHAINS TO THE STONE HE SET FOR THE BEGINNING OF THE WIDE PORTION OF ROAD; THEN CONTINUES WEST ON THE SECTION LINES FOR 6.25 CHAINS TO THE STONE HE SET FOR THE END OF THE WIDE PORTION OF ROAD; THEN CONTINUES WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-21-10 AT THE TERMINUS OF THIS ROAD SURVEY

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 622 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 357 THROUGH 360 PETITION BY P. E. LAMOUREUX AND OTHERS FOR THE LOCATION AND VACATION OF A ROAD IN TOWNSHIP 21-10 [PACKET 767 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 24, 1906, AND WAS GRANTED ON THE SECTION LINE AND 40 FOOT WIDE ROAD, 20 FEET EACH SIDE OF THE SURVEYED LINE, EXCEPTING THAT PORTION BETWEEN THE STONES HE SET BETWEEN SECTIONS 22-21-10 AND 27-21-10, WHICH IS 65 FEET WIDE, 20 FEET ON THE NORTH AND 45 FEET ON THE SOUTH SIDE OF THE SECTION LINE. ON JANUARY 10, 1907 BY H. W. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 11, 1907 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE 1/4 CORNER STONE IN PLACE AND ON LINE WITH A FENCE TO THE SOUTH** AT THE NORTH 1/4 CORNER OF SECTION 26-21-10 ON THIS ROAD SURVEY. THE OLD ROAD BETWEEN THE BEGINNING AND THE TERMINUS OF THIS NEW ROAD WAS **VACATED.**

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT 23 FEET EAST AND 19 FEET SOUTH OF FENCES AT THE NORTHEAST CORNER OF SECTION 26-21-10 TO BEGIN THIS ROAD SURVEY

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) THIS ROAD EXTENDS WEST ON THE SECTION LINES TO THE GOVERNMENT STONE AT 20 FEET WEST AND 20 FEET SOUTH OF A FENCE CORNER AT THE NORTHWEST CORNER OF SECTION 26-21-10; THEN CONTINUES WEST ON THE SECTION LINES FOR 38.25 CHAINS TO THE STONE HE SET FOR THE BEGINNING OF THE WIDE PORTION OF ROAD; THEN CONTINUES WEST ON THE SECTION LINES FOR 6.25 CHAINS TO THE STONE HE SET FOR THE END OF THE WIDE PORTION OF ROAD; THEN CONTINUES WEST ON THE SECTION LINES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 27-21-10 AT THE TERMINUS OF THIS ROAD SURVEY

NORTH QUARTER CORNER 26-21-10