

NORTHWEST CORNER SECTION 29, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 267 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 11" X 4"** FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-21-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.52 CHAINS EAST TO THE 22" X 10" X 4" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 29-21-10
 - 2) 79.04 CHAINS EAST TO THE 28" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-21-10

- 2) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-10 SHOWS A **STONE** AT THE "NE CORNER SECTION 30-21-10".
 - 1) 1" IRON PIN ON THE EAST SIDE OF THE STONE
 - 2) STONE HAS 5 MARKS ON THE EAST SIDE; 2 MARKS ON THE SOUTH SIDE; AND "R" ON THE EAST SIDE

NORTHWEST CORNER 29-21-10