

**NORTH 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 33, TOWNSHIP 21 SOUTH, RANGE 10 EAST**

1) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 1, 2015 FOR THE SURVEY OF THE EAST HALF OF THE SOUTHEAST QUARTER AND THE SOUTH HALF OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 28-21-10 FOR BENNETT/MORAN, SURVEY F28002 IN THE SURVEY FILE FOR TOWNSHIP 21-10, SAID THAT **HE SET A 1/2" X 24" IRON PIN WITH HIS "PS 752" PINK CAP** AT THE SOUTH 1/16<sup>TH</sup> CORNER OF THE SOUTHEAST 1/4 OF SECTION 28-21-10 ON TRUE LINE BETWEEN THE SOUTHEAST AND SOUTH SECTION CORNERS ON THIS SURVEY.

- 1) 16.5' EAST TO A FENCE NORTH-SOUTH
- 2) 657.39' NORTH TO A 1/2" IRON PIN [NORTHWEST CORNER S1/2 OF SE1/4 OF SE1/4]
- 3) 1,330.08' EAST TO STONE [SOUTHEAST CORNER SE1/4]
- 4) 1,330.08' WEST TO 1/2" IRON PINE [SOUTHWEST CORNER SE1/4]
- 5) FALLS ON WEST SLOPE

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,330.08' WEST TO THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 28-21-10
- 2) 1,330.08' EAST TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 28-21-10
- 3) 657.39' NORTH TO THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE S1/2 OF THE SE1/4 OF THE SE1/4 OF SECTION 28-21-10
- 4) 1,314.78' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE N1/2 OF THE SE1/4 OF THE SE1/4 OF SECTION 28-21-10
- 5) 2,629.57' NORTH TO THE 1/2" X 24" IRON PIN HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 28-21-10

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 33-21-10