

NORTH 1/4 CORNER SECTION 34, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 256 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 21" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-21-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.84 CHAINS WEST TO THE 18" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-21-10
 - 2) 39.84 CHAINS EAST TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-21-10

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 1991, FOR JOB NUMBER 91080, SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A TRACT OF 0.731 ACRES FOR ADDITIONAL RIGHT-OF-WAY FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT DUE TO THE MOVEMENT OF THE VERDIGRIS RIVER, SAID THAT HE EXCAVATED WITH A COUNTY BACKHOE AND **HE FOUND THE 5" X 10" LIMESTONE ABOUT 10" DEEP** AT THE SOUTH 1/4 CORNER OF SECTION 27-21-10. HE DROVE CAPPED REBARS ON THE NORTH AND SOUTH SIDES OF THE STONE, AND **HE SET A RAILROAD SPIKE OVER THE TOP OF THE STONE**. THE STONE WAS FOUND TO BE IN LINE WITH THE EVIDENCE OF AN OLD FENCE TO THE SOUTH AND IT FELL 0.95' NORTH OF THE LINE BETWEEN THE STONES THAT HE FOUND AT THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 27-21-10.
 - 1) 35.0' NE TO A PK NAIL & WASHER IN A CORNER FENCE POST
 - 2) 45.5' SE TO A PK NAIL & WASHER IN A FENCE POST
 - 3) 24.0' SOUTH TO A PK NAIL IN A CORNER FENCE POST
 - 4) 14.0' EAST TO A FENCE LINE TO THE NORTH
 - 5) 3.5' NORTH TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROADHIS SURVEY DRAWING AND FIELD NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,636.38' WEST TO THE GLO LIMESTONE HE FOUND AT THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 27-21-10
 - 2) 2,638.32' EAST TO THE LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 27-21-10

NORTH QUARTER CORNER 34-21-10