

NORTHWEST CORNER SECTION 34, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 255 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE CORNER TO SECTIONS 27, 28, 33 & 34-21-10 ON JUNE 5, 1857.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 33 & 34-21-10
 - 2) 80.00 CHAINS SOUTH TO THE 24" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 33 & 34-21-10 ON THE SOUTH TOWNSHIP LINE AND THE SOUTH COUNTY LINE
 - 3) 39.84 CHAINS EAST TO THE 21" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 27 & 34-21-10
 - 4) 79.68 CHAINS EAST TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-21-10

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 6, 1991, FOR JOB NUMBER 91080, SURVEY F27001 IN THE SURVEY FILE FOR TOWNSHIP 20-10 FOR A TRACT OF 0.731 ACRES FOR ADDITIONAL RIGHT-OF-WAY FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT DUE TO THE MOVEMENT OF THE VERDIGRIS RIVER, SAID THAT **HE FOUND THE 3" X 12" X 18" GLO LIMESTONE STANDING** AT THE SOUTHWEST CORNER OF SECTION 27-21-10, STANDING ON THE HIGH BLUFF OVERLOOKING THE RIVER AND PROPERLY NOTCHED.
 - 1) REBARS WERE SET ON THE EAST AND WEST SIDES OF THE STONE
 - 2) IN LINE WITH A FENCE TO THE SOUTH [EXTENDED]HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,636.38' EAST TO THE LIMESTONE HE FOUND AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 27-21-10
 - 2) 5,274.70' EAST TO THE LIMESTONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 27-21-10

- 3) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 1, 2015 FOR THE SURVEY OF THE EAST HALF OF THE SOUTHWEST QUARTER AND THE SOUTH HALF OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 28-21-10 FOR BENNETT/MORAN, SURVEY F28002 IN THE SURVEY FILE FOR TOWNSHIP 21-10, SAID THAT **HE FOUND THE EXISTING RECORD 3" X 12" X 18" GLO LIMESTONE WITH SLASH MARKS ON THE SOUTH AND EAST SIDE OF A TRAIL** AT THE SOUTHWEST CORNER OF SECTION 28-21-10 FROM HIS EXISTING REFERENCE TIES ON FILE FROM HIS PREVIOUS SURVEY IN 1991 FOR PROJECT NUMBER 91080.
 - 1) 1/2" IRON PIN ON EAST SIDE OF STONE WITH REMAINS OF RED CAP, 1/2" IRON PIN ON WEST SIDE OF STONE
 - 2) 4.35' SE TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
 - 3) 24.4' WNW TO A CONCRETE NAIL & BOTTLECAP IN THE NORTH SIDE OF A 16" OAK TREE
 - 4) 34.1' WSW TO A CONCRETE NAIL & BOTTLECAP IN THE SOUTH SIDE OF A 18" DOUBLE OAK TREE
 - 5) IN LINE WITH A FENCE TO THE SOUTH EXTENDED
 - 6) 2,660.15' WEST TO A 1/2" IRON PIN [SOUTH QUARTER CORNER SECTION 28]HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,330.08' WEST TO THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SE1/4 OF SECTION 28-21-10

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 2,660.16' WEST TO THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 28-21-10
- 3) 657.42' NORTH TO THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE SE1/4 OF THE SE1/4 OF SECTION 28-21-10
- 4) 1,314.84' NORTH TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF THE N1/2 OF THE SE1/4 OF THE SE1/4 OF SECTION 28-21-10
- 5) 2,629.68' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE NE1/4 OF THE SE1/4 OF SECTION 28-21-10
- 6) 5,269.68' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 28-21-10

NORTHWEST CORNER 34-21-10