

NORTH 1/4 CORNER SECTION 35, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ON PAGE 251 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 11" X 3-1/2"** FOR THE 1/4 CORNER BETWEEN SECTIONS 26 & 35-21-10.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.02-1/2 CHAINS WEST TO THE 22" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 26, 27, 34 & 35-21-10
 - 2) 40.02-1/2 CHAINS EAST TO THE 25" X 16" X 3" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 25, 26, 35 & 36-21-10

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 45, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 45 DATED JUNE 24, 1884 AT THE REQUEST OF E. W. PILE TO ESTABLISH THE EAST LINE OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 35-21-10, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 35-21-10 ON THIS SURVEY.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,321' WEST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF THE W1/2 OF THE NW1/4 OF SECTION 35-21-10
 - 2) 2,642' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-21-10

- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 170, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "F" ON PAGE 134 DATED JULY 16-20, 1888 AT THE REQUEST OF L. NEWMAN TO ESTABLISH THE CORNERS OF THE NORTHEAST 1/4 AND THE LINE BETWEEN THE SOUTHEAST 1/4 AND THE SOUTHWEST 1/4 OF SECTION 35-21-10, SAID THAT **HE SET A 20" X 12" X 3" LIMESTONE MARKED "1/4" ON THE NORTH FACE** FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 35-21-10 ON LINE AND HALFWAY BETWEEN THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-21-10 AND THE OLD GOVERNMENT STONE THAT HE FOUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 35-21-10 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 2,634.35' WEST TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-21-10
 - 2) 2,634.35' EAST TO THE OLD GOVERNMENT STONE HE FOUND LYING LOOSE IN THE GROUND AND **HE RESET** FOR THE PERMANENT NORTHEAST CORNER OF SECTION 35-21-10
 - 3) 7,923.15' EAST TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 36-21-10 ON THE RANGE LINE

- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-10 SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 26-21-10".
 - 1) FIELD BOOK NUMBER 35
 - 2) FIELD BOOK NUMBER 32

- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-10 SHOWS A **STONE & PIN** AT THE "N1/4 CORNER SECTION 35-21-10".
 - 1) 32.35' MIDWAY BETWEEN FENCE POSTS [CORNER POST ON THE NORTH AND AN OLD POST ON THE SOUTH]
 - 2) 44.40' NE TO A SPIKE IN A TELEPHONE POLE

NORTH QUARTER CORNER 35-21-10