

WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 35, TOWNSHIP 21 SOUTH, RANGE 10 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 580 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 189 THROUGH 192 PETITION BY W. W. COVERT AND OTHERS FOR A ROAD BETWEEN SECTIONS 34 & 35-21-10 THAT HE SURVEYED ON NOVEMBER 25, 1902, WAS ESTABLISHED AT 40 FEET WIDE ON THE SECTION LINE AND 60 FEET FOR THE PORTION THAT DEVIATES FROM THE SECTION LINE, ON FEBRUARY 5, 1903 AS NOTED BY E. MOORHEAD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY H. E. PEACH, COUNTY CLERK, AND RECORDED ON FEBRUARY 14, 1903 BY ALVA J. SMITH, COUNTY SURVEYOR, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE EAST 1/8TH CORNER OF THE NORTHEAST 1/4 OF SECTION 34-21-10. SEE THE SURVEY FOR THE CENTERLINE OF THIS ROAD THAT BEGAN AT THE SOUTHEAST CORNER OF SECTION 34-21-10 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE, THEN EXTENDS NORTH ON THE SECTION LINE AT N. 8°35' W. [MAGNETIC MERIDIAN] FOR 32.50 CHAINS AT 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE, THENCE N. 57°30' W. FOR 3.00 CHAINS AT 60 FEET WIDE, THENCE N. 5°50' W. FOR 6.00 CHAINS AT 60 FEET WIDE, THENCE N. 33°50' E. FOR 2.70 CHAINS AT 60 FEET WIDE TO THE SECTION LINE, THENCE NORTH ON THE SECTION LINE AT 40 FEET WIDE, 20 FEET EACH SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 34-21-10 TO END THIS ROAD SURVEY.

- 2) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, BY J. MAX YINGLING, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 77 AT THE REQUEST OF J. E. CROWELL REQUIRING HIM TO MAKE A SURVEY OF TH LINE BETWEEN HIM AND THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 35-21-10, SAID THAT **HE FOUND A STONE** SUPPOSED TO BE THE SOUTHWEST CORNER OF THE NORTHWEST 1/4 OF THE NORTHWEST 1/4 OF SECTION 35-21-10 ON THIS **PERMANENT SURVEY**. AFTER HE RAN THE SECTION LINES FROM THE STONE THAT HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-21-10 SOUTH TO THE STONE THAT HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-21-10, HE SAID THAT MEASUREMENTS SHOWED THAT THE STONE WAS 2.48' SOUTH OF ITS PROPER POSITION, BUT AS IT WAS IN LINE WITH AN OLD HEDGE RUNNING EAST AND THE HEDGE APPEARED TO HAVE BEEN GROWING IN ITS PRESENT PLACE FOR MORE THAN FIFTEEN YEARS AND AS IT WAS ALLEGED BY SEVERAL WITNESSES THAT THE STONE HAD BEEN IN ITS PRESENT LOCATION FOR A GREAT MANY YEARS OR AS LONG AS ANY OF THEM HAD ANY KNOWLEDGE OF SAID STONE, HE DEEMED THE STONE TO BE IN ITS ORIGINAL POSITION AND THAT **THE STONE FOUND WAS THE LEGAL CORNER**. THE SURVEY WAS MADE NOVEMBER 29, 1910 AND WAS ENTERED DECEMBER 30, 1910.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,323.4' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 35-21-10
 - 2) 1,320.1' SOUTH TO THE THEORETICAL LOCATION FOR THE WEST 1/4 CORNER OF SECTION 34-21-10
 - 3) 3,960.3' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 35-21-10 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE
 - 4) 1,321.4' EAST TO THE 15" X 8" X 7' LIMESTONE ROCK WITH A CROSS ON THE TOP HE PLANTED FOR THE PERMANENT SOUTHEAST CORNER OF THE NW1/4 OF THE NW1/4 OF SECTION 35-21-10

WEST SIXTEENTH CORNER NORTHWEST QUARTER 35-21-10