

WEST 1/4 CORNER SECTION 02, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 415 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 27" X 17" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-21-11 ON NOVEMBER 27, 1856. THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 43.86 CHAINS NORTH TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE CLOSING CORNER BETWEEN SECTIONS 2 & 3-21-11 ON THE 4TH STANDARD PARALLEL AND THE NORTH TOWNSHIP BOUNDARY
 - 2) 40.00 CHAINS SOUTH TO THE 24" X 14" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-11

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 21-11 FOR FOUR TRACTS COMPRISING THE OLPE CITY LAKE LOCATED IN PARTS OF THE NORTHEAST QUARTER, THE SOUTHEAST QUARTER, AND THE SOUTHWEST QUARTER OF SECTION 3 AND PART OF THE NORTHWEST QUARTER OF SECTION 10, ALL IN TOWNSHIP 21 SOUTH, RANGE 11 EAST FOR PROJECT NUMBER 87068 DATED AUGUST 1, 1988, SAID IN HIS *REPORT OF SURVEY* THAT **HE FOUND A 1/2" REBAR** AT THE EAST 1/4 CORNER OF SECTION 3-21-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.

- 3) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED AUGUST 19, 2015, FOR PROJECT NUMBER 15180-02, A SURVEY OF THREE PARCELS IN THE EAST ONE HALF OF THE FRACTIONAL NORTHEAST QUARTER OF SECTION 3-21-11 FOR HAAG, MEDENCIY AND HAMMOND, SURVEY F03008 IN THE SURVEY FILE FOR TOWNSHIP 21-11, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" IRON PIN AT 1" ABOVE THE SURFACE** AT THE EAST 1/4 CORNER OF SECTION 3-21-11. HE NOTED THAT THE ORIGIN IS UNCERTAIN; IT IS VERY LIKELY THE IRON PIN FROM SURVEYS DONE BY L. M. GOULD, P.S. 142, AND LLOYD DOBLER, P.S. 541.
 - 1) 21.40' NORTH TO A CONCRETE NAIL & BOTTLECAP IN A GATE FENCE POST
 - 2) ON THE NORTH SIDE OF A CORNER FENCE POST
 - 3) IN LINE WITH THE FENCE TO THE NORTH THE EAST AND THE WEST
 - 4) NO OTHER TIES AVAILABLEHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,428.15' NORTH TO THE SOUTHEAST CORNER OF THE HAAG PARCEL AS MARKED BY THE 1/2" X 24" IRON PIN WITH HIS "PS 752 s. BROSEMER" CAP
 - 2) 1,678.15' NORTH TO THE NORTHEAST CORNER OF THE HAAG PARCEL AS MARKED BY THE 1/2" X 24" IRON PIN WITH HIS "PS 752 s. BROSEMER" CAP
 - 3) 2,891.97' NORTH TO THE 5/8" IRON PIN WITH A LYON COUNTY CAP SET IN A DRILL HOLE AT THE NORTHEAST CORNER OF THE FRACTIONAL NE1/4 OF SECTION 3-21-11 ON THE 4TH STANDARD PARALLEL

WEST QUARTER CORNER 02-21-11