

WEST 1/4 CORNER SECTION 03, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 420 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 23" X 15" X 6"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 4-21-11.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 42.96 CHAINS NORTH TO THE 25" X 12" X 7" LIMESTONE THEY SET FOR THE CORNER BETWEEN SECTIONS 3 & 4-21-11 ON THE 4TH STANDARD PARALLEL
- 2) 40.00 CHAINS SOUTH TO THE 17" X 13" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 4, 9 & 10-21-11

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 43, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 42 DATED JUNE 13, 1870 TO ESTABLISH THE CENTER CORNER OF SECTION 4-21-11 AND TO DIVIDE THE NORTHEAST 1/4 OF SAID SECTION 4 BY A LINE RUNNING EAST & WEST, SAID THAT **HE FOUND A STONE** AT THE EAST 1/4 CORNER OF SECTION 4-21-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) 1,318-1/2' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NE1/4 OF SECTION 4-21-11
- 2) 2,833-1/2' NORTH TO THE STONE MARKED "CC" HE FOUND AT THE NORTHEAST CLOSING CORNER OF SECTION 4-21-11 ON THE 4TH STANDARD PARALLEL
- 3) 2,640-1/2' WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 4-21-11
- 4) 5,281' WEST TO THE STONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 4-21-11

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 151, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 151 DATED NOVEMBER 18, 1886 ORDERED BY J. H. BANGS TO LOCATE THE NORTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 3-2-11, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 3-21-11 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,312.5' EAST TO THE 4" X 8" X 16" LIMESTONE HE SET FOR THE PERMANENT NORTHEAST CORNER OF THE W1/2 OF THE SW1/4 OF SECTION 3-21-11
- 2) 2,625' EAST TO THE STONE HE FOUND AT THE CENTER CORNER OF SECTION 3-21-11

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F10001 IN THE SURVEY FILE FOR TOWNSHIP 21-11 FOR FOUR TRACTS COMPRISING THE OLPE CITY LAKE LOCATED IN PARTS OF THE NORTHEAST QUARTER, THE SOUTHEAST QUARTER, AND THE SOUTHWEST QUARTER OF SECTION 3 AND PART OF THE NORTHWEST QUARTER OF SECTION 10, ALL IN TOWNSHIP 21 SOUTH, RANGE 11 EAST FOR PROJECT NUMBER 87068 DATED AUGUST 1, 1988, SAID IN HIS *REPORT OF SURVEY* THAT **HE FOUND THE BOTTOM PART OF THE GLO SANDSTONE ALONG WITH A STAKE** AT THE WEST 1/4 CORNER OF SECTION 3-21-11. **HE SET REBARS ON THE EAST AND WEST SIDES OF THE STONE**. THE FOLLOWING TIES ARE ON THE SURVEY:

- 1) 24.5' SW TO A PK NAIL & WASHER IN AN ELM TREE
- 2) 26.0' WEST TO A LINE OF FENCE NORTH-SOUTH
- 3) 28.0' EAST TO A LINE OF FENCE NORTH-SOUTH
- 4) 4.0' NORTH TO A LINE OF FENCE TO THE WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS TIES ARE ON PAGE 2

- 1) 2,841.54' NORTH TO THE SPIKE IN ASPHALT HE FOUND AT THE NORTHWEST CORNER OF SECTION 3-21-11 ON THE 4TH STANDARD PARALLEL
 - 2) 1,317.41' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 3-21-11
 - 3) 2,634.82' EAST TO THE REBAR & PIPE HE FOUND AT THE CENTER CORNER OF SECTION 3-21-11
 - 4) 2,637.91' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-21-11
 - 5) 3,957.18' SOUTH TO THE THEORETICAL POSITION FOR THE WEST 1/16TH CORNER OF THE NW1/4 OF SECTION 10-21-11
 - 6) 5,276.45' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 10-21-11
 - 7) SURVEY COORDINATES: NORTH = 8450.93 EAST = 2510.11
- 5) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 23, 1996, FOR PROJECT NUMBER 96-4N, TO REPLACE THE EXISTING 16 FOOT CONCRETE CULVERT 943.0-540.6 WITH A 30 FOOT ALL STEEL BRIDGE, **FOUND THE BOTTOM PART OF THE GLO SANDSTONE AT 12" BELOW THE ROAD SURFACE WITH 1/2" REBARS ON THE EAST AND WEST SIDES OF THE STONE** AT THE WEST 1/4 CORNER OF SECTION 3-21-11 FROM EXISTING TIES OF RECORD IN THE COUNTY ENGINEER'S OFFICE BY STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, DATED AUGUST 1, 1988.
- 1) 34.3' NE TO A WIRE AND WASHER TIED TO A STEEL FENCE POST
 - 2) 30.1' EAST TO A WIRE AND 2 WASHERS TIED TO A STEEL FENCE POST
 - 3) 26.3' NW TO A WIRE AND WASHER TIED TO A 3" DIAMETER STEEL PIPE POST
 - 4) IN THE TRAVELED WAY OF THE NORTH-SOUTH GRAVEL COUNTY ROAD "K"
 - 5) 4' NORTH TO FENCE LINES TO THE EAST AND WEST
- PROJECT PLANS SHOWS THE FOLLOWING INFORMATION:
- 1) FOUND THE GLO SANDSTONE AT 12" BELOW THE SURFACE OF THE GRAVEL ROAD WITH 1/2" REBARS ON THE EAST AND WEST SIDES OF THE STONE AT THE WEST 1/4 CORNER OF SECTION 3-21-11 AT CENTERLINE STATION 300+00.00
 - 2) 448.92' SOUTH TO THE 5/8" X 24" REBAR WITH A LYON COUNTY CAP SET 6" BELOW THE SURFACE ON THE SECTION LINE AT CENTERLINE STATION 295+51.08

WEST QUARTER CORNER 03-21-11