

**NORTHWEST CORNER SECTION 07, TOWNSHIP 21 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 109 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 12" X 3"** FOR THE CORNER TO SECTIONS 6 & 7-21-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 27, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 6-21-11
- 2) 82.50 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 32" X 14" X 3" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIP 21 SOUTH, RANGES 10 & 11 EAST AT THE NORTHWEST CORNER OF SECTION 6-21-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL
- 3) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 9" X 3" SANDSTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 7-21-11
- 4) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 32" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-21-11
- 5) 34.71 CHAINS EAST TO THE 18" X 13" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 6 & 7-21-11
- 6) 74.71 CHAINS EAST TO THE 22" X 12" X 7" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-21-11

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN SURVEY NUMBER 171, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 113 DATED AUGUST 15, 1888 FOR A ROAD IN TOWNSHIP 21, RANGES 10 & 11, SAID THAT **HE SET A STONE 18" X 10" X 2" MARKED "R/1M"** AT 1 MILE EAST OF THE STONE HE SET AT THE NORTHWEST CORNER OF SECTION 12-21-10 TO BEGIN THIS ROAD SURVEY. HE NOTED THAT THIS ROAD IS 50 FEET WIDE, 25 FEET EACH SIDE OF THE SECTION LINE, EXCEPT ON THE SOUTH LINE OF SECTION 6-21-11 WHERE HE KEPT THE ENTIRE WIDTH OF THE ROAD ON THE SOUTH SIDE OF A HEDGE ROW. HE DOES **NOT** CALL THIS ROAD STONE THE NORTHWEST CORNER OF SECTION 7-21-10 ON THE RANGE LINE.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE 14" X 8" X 3" ROAD STONE MARKED "R" HE SET FOR THE NORTHWEST CORNER OF SECTION 12-21-10 TO BEGIN THIS ROAD SURVEY.
- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES, LEAVING THE HEDGE ROW ON THE NORTH AS THE NORTH LINE OF THE ROAD, FOR 1 MILE TO THE 20" X 10" X 3" ROAD STONE MARKED "R/2M" HE SET, THEN CONTINUES EAST ON THE SECTION LINES FOR 1 MILE TO THE 12" X 10" X 1-1/2" SANDSTONE MARKED "R/3M" HE SET FOR THE TERMINUS OF THIS ROAD SURVEY AT THE SOUTHEAST CORNER OF SECTION 5-21-11

- 3) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 363 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 402 TO 404 PETITIONED BY L. W. OSTROM AND OTHERS FOR A ROAD IN TOWNSHIPS 21-10 AND 21-11 [PACKET 609 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 15, 1888, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON OCTOBER 2, 1888 AS NOTED BY J. S. GRIMSLEY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JANUARY 30, 1889 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE SET AN 18" X 10" X 2" STONE MARKED "R/1M"** AT ONE MILE EAST OF THE 14" X 8" X 3" STONE MARKED "R" HE SET AT THE NORTHWEST CORNER OF SECTION 12-21-10 TO BEGIN THIS ROAD SURVEY. HE DOES **NOT** CALL THIS ROAD STONE THE NORTHWEST CORNER OF SECTION 6-21-11 ON THE RANGE LINE.

HIS INFORMATION IS CONTINUED ON PAGE 2

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 1 MILE TO THE 14" X 8" X 3" ROAD STONE MARKED "R" HE SET FOR THE NORTHWEST CORNER OF SECTION 12-21-10 TO BEGIN THIS ROAD SURVEY.
  - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES, LEAVING THE HEDGE ROW ON THE NORTH AS THE NORTH LINE OF THE ROAD, FOR 1 MILE TO THE 20" X 10" X 3" ROAD STONE MARKED "R/2M" HE SET, THEN CONTINUES EAST ON THE SECTION LINES FOR 1 MILE TO THE 12" X 10" X 1-1/2" SANDSTONE MARKED "R/3M" HE SET FOR THE TERMINUS OF THIS ROAD SURVEY AT THE SOUTHEAST CORNER OF SECTION 5-21-11
- 4) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED MAY 30, 2001, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE WEST FRACTIONAL HALF OF SECTION 7-21-11 FOR CLIFF COLE, SAID IN HIS *REPORT OF SURVEY* THAT HE EXCAVATED WITH A COUNTY BACK-HOE AND **HE FOUND A 3" X 12" LIMESTONE** AT THE NORTHWEST CORNER OF SECTION 7-21-11 ON THE RANGE LINE. **HE PLACED A 1/2" REBAR WITH HIS "LS 82" CAP OVER THE TOP CENTER OF THE STONE.**
- 1) 30.9' SW TO THE NEAR FACE OF A POWER POLE
  - 2) 59.2' NNE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
  - 3) 32.5' EAST TO A LINE OF FENCE TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,630.36' EAST TO THE NORTHWEST CORNER OF TRACT #2, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET AT 25' SOUTH ON THE SOUTH ROAD EASEMENT LINE
- 2) 2,290.36' EAST TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF SECTION 7-21-11, AND THE P.O.B. OF TRACT #2
- 3) 4,929.86' EAST TO THE 1-1/2" X 10" X 12" SANDSTONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-21-11, WITH A 1/2" REBAR WITH HIS "LS 82" CAP HE SET OVER THE CENTER OF THE STONE
- 4) 1,791.05' SOUTH ON THE RANGE LINE TO THE NORTHWEST CORNER OF TRACT #3 AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET AT 25' EAST
- 5) 3,917.37' SOUTH ON THE RANGE LINE TO THE P.O.B. OF TRACT #3, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET AT 25' EAST
- 6) 5,272.13' SOUTH ON THE RANGE LINE TO THE 5/8" REBAR HE FOUND OVER THE STONE AT THE SOUTHWEST CORNER OF SECTION 7-21-12

NORTHWEST CORNER 07-21-11