

WEST 1/4 CORNER SECTION 08, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 432 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 11" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 8-21-11.
- 2) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-11 SHOWS A **STONE** AT THE WEST 1/4 CORNER OF SECTION 8-21-11.
 - 1) 25' EAST TO A CORNER FENCE POST
- 3) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED MAY 30, 2001, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE WEST FRACTIONAL HALF OF SECTION 7-21-11 FOR CLIFF COLE, SAID ON HIS *REPOT OF SURVEY* THAT HE EXCAVATED WITH A COUNTY BACKHOE FOR THE STONE AT THE EAST 1/4 CORNER OF SECTION 7-21-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **OBLITERATED**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 82" CAP** FOR THE EAST 1/4 CORNER OF SECTION 7-21-11 IN LINE WITH THE OLD FENCES TO THE EAST AND WEST AND IN THE CENTER OF THE NORTH-SOUTH ROAD RIGHT-OF-WAY.
 - 1) IN LINE WITH AN OLD FENCE TO THE EAST
 - 2) IN LINE WITH AN OLD FENCE TO THE WEST
 - 3) 19.8' EAST TO THE NEAR FACE OF A CORNER FENCE POST
 - 4) 19.8' WEST TO THE NEAR FACE OF A CORNER FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 2,639.36' NORTH TO THE 1-1/2" X 10" X 12" SANDSTONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 7-21-11, WITH A 1/2" REBAR WITH HIS "LS 82" CAP HE SET OVER THE CENTER OF THE STONE
 - 2) 2,643.95' SOUTH TO THE 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-21-11

WEST QUARTER CORNER 08-21-11