

**NORTH 1/4 CORNER SECTION 10, TOWNSHIP 21 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 419 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 10" X 8"** FOR THE 1/4 CORNER BETWEEN SECTIONS 3 & 21-11.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.94 CHAINS WEST TO THE 17" X 13" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-21-11
- 2) 39.94 CHAINS EAST TO THE 24" X 14" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-11

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 153, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 235 DATED JULY 17, 1906 FOR A ROAD IN TOWNSHIP 21, RANGE 11 FOR VAL FREITAG, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE BETWEEN CORNER POINTS** AT THE NORTH 1/4 CORNER OF SECTION 10-21-11 ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) THE ROAD ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 40.01 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 10-21-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY; THE ROAD NOT ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 40.14 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-21-11; THENCE CONTINUES WEST ON THE SECTION LINES FOR 40.06 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-21-11 ON LINE WITH A FENCE EAST. 45 LINKS WEST OF A FENCES, AND 43 LINKS EAST OF FENCES
- 2) THE ROAD ALLOWED ON THIS ROAD SURVEY EXTENDS EAST ON THE SECTION LINES FOR 19.82 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 3-21-11 AT 36 LINKS EAST OF A FENCE AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY

- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 617 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 337 THROUGH 340 PETITIONED BY VAL FREITAG AND OTHERS FOR A ROAD IN TOWNSHIP 21-11 BEGINNING AT THE SOUTHWEST CORNER OF SECTION 4-2-11 THENCE EAST ON THE SECTION LINES FOR ONE AND 3/4 MILES TO A PUBLIC ROAD [PACKET 753 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 17, 1906, WAS GRANTED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE SURVEYED LINE, FOR THE LAST 3/4 OF A MILE ONLY, THE FIRST MILE WAS **NOT** GRANTED BY THE COMMISSIONERS ON SEPTEMBER 6, 1906 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON SEPTEMBER 12, 1906 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE** AT THE NORTH 1/4 CORNER OF SECTION 10-21-11 ON THE ROAD ALLOWED ON THIS ROAD SURVEY.

HIS SURVEY NOTES /DRAWING SHOW THE FOLLOWING INFORMATION:

- 1) THE ROAD ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 40.01 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 10-21-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY; THE ROAD NOT ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 40.14 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-21-11; THENCE CONTINUES WEST ON THE SECTION LINES FOR 40.06 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-21-11 ON LINE WITH A FENCE EAST. 45 LINKS WEST OF A FENCES, AND 43 LINKS EAST OF FENCES

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) THE ROAD ALLOWED ON THIS ROAD SURVEY EXTENDS EAST ON THE SECTION LINES FOR 19.82 CHAINS TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 3-21-11 AT 36 LINKS EAST OF A FENCE AT THE TERMINUS OF THE ROAD ALLOWED ON THIS ROAD SURVEY
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 20, 1989, FOR THE OLPE LAKE BOUNDARY SURVEY, SURVEY F10007 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR FOUR TRACTS COMPRISING THE OLPE CITY LAKE, LOCATED IN PARTS OF THE NORTHEAST QUARTER, THE SOUTHEAST QUARTER AND THE SOUTHWEST QUARTER OF SECTION 3, AND PART OF THE NORTHWEST QUARTER OF SECTION 10, ALL IN TOWNSHIP 21, RANGE 11, SAID IN HIS *REPORT OF SURVEY* THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 10-21-11, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP FOR THE SOUTH 1/4 CORNER OF SECTION 3-21-11 ON TRUE LINE BETWEEN THE STONE THAT HE FOUND AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-21-11 AND THE 1/2" CAPPED REBAR HE SET FOR THE SOUTHWEST CORNER OF SECTION 3-21-11, AND AT THE PRORATED POSITION OF ALVA J. SMITH'S 1906 SURVEY.**
  - 1) 0.4' NORTH TO THE EAST FACE OF A CORNER FENCE POST
  - 2) 24.6' WEST TO A PK NAIL & WASHER IN THE BASE OF A 24" DIA. CLUMP HEDGE
  - 3) 37.1' NNW TO A PK NAIL & WASHER IN THE BASE OF A 16" DIA. HEDGE TREE
  - 4) IN LINE WITH A FENCE TO THE SOUTH

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

  - 1) 240.74' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
  - 2) 1,020.74' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
  - 3) 1,320.74' WEST TO THE THEORETICAL POSITION FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 3-21-11
  - 4) 1,870.74' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
  - 5) 2,641.48' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-21-11
  - 6) 1,308.52' EAST TO THE LIMESTONE HE FOUND AT THE SOUTHEAST CORNER OF THE W1/2 SE1/4 OF SECTION 3-21-11
  - 7) 1,319.93' SOUTH TO THE THEORETICAL POSITION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 10-21-11
  - 8) 2,639.86' SOUTH TO THE THEORETICAL POSITION FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 10-21-11
  - 9) 2,633.81' NORTH TO THE REBAR AND PIPE HE FOUND AT THE NORTHEAST CORNER OF THE SW1/4 [CENTER] OF SECTION 3-21-11
  - 10) SURVEY COORDINATES: NORTH = 5785.065      EAST = 5149.95

NORTH QUARTER CORNER 10-21-11