

NORTH 1/16TH CORNER OF THE NORTHEAST QUARTER OF SECTION 10, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 153, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 235 DATED JULY 17, 1906 FOR A ROAD IN TOWNSHIP 21, RANGE 11 FOR VAL FREITAG, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE AT 36 LINKS EAST OF A FENCE** AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-21-11 TO END THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD. HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) THE ROAD ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 19.82 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-21-11; THENCE WEST ON THE SECTION LINES FOR 40.01 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 10-21-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY; THE ROAD NOT ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 40.14 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-21-11; THENCE CONTINUES WEST ON THE SECTION LINES FOR 40.06 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-21-11 ON LINE WITH A FENCE EAST. 45 LINKS WEST OF A FENCES, AND 43 LINKS EAST OF FENCES

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 617 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 337 THROUGH 340 PETITIONED BY VAL FREITAG AND OTHERS FOR A ROAD IN TOWNSHIP 21-11 BEGINNING AT THE SOUTHWEST CORNER OF SECTION 4-2-11 THENCE EAST ON THE SECTION LINES FOR ONE AND 3/4 MILES TO A PUBLIC ROAD [PACKET 753 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JULY 17, 1906, WAS GRANTED AS A 50 FOOT WIDE ROAD, 25 FEET ON EACH SIDE OF THE SURVEYED LINE, FOR THE LAST 3/4 OF A MILE ONLY, THE FIRST MILE WAS NOT GRANTED BY THE COMMISSIONERS ON SEPTEMBER 6, 1906 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON SEPTEMBER 12, 1906 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE AT 36 LINKS EAST OF A FENCE** AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-21-11 TO END THE ROAD ALLOWED ON THIS ROAD SURVEY. HIS SURVEY NOTES /DRAWING SHOW THE FOLLOWING INFORMATION:
 - 2) THE ROAD ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 19.82 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-21-11; THENCE WEST ON THE SECTION LINES FOR 40.01 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 10-21-11 TO BEGIN THE ROAD ALLOWED ON THIS ROAD SURVEY; THE ROAD NOT ALLOWED EXTENDS WEST ON THE SECTION LINES FOR 40.14 CHAINS TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 9-21-11; THENCE CONTINUES WEST ON THE SECTION LINES FOR 40.06 CHAINS TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 9-21-11 ON LINE WITH A FENCE EAST. 45 LINKS WEST OF A FENCES, AND 43 LINKS EAST OF FENCES

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED FEBRUARY 20, 1989, SURVEY F10007 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR FOUR TRACTS COMPRISING THE OLPE CITY LAKE, LOCATED IN PARTS OF THE NORTHEAST QUARTER, THE SOUTHEAST QUARTER AND THE SOUTHWEST QUARTER OF SECTION 3, AND PART OF THE NORTHWEST QUARTER OF SECTION 10, ALL IN TOWNSHIP 21, RANGE 11, SAID IN HIS *REPORT OF SURVEY* THAT **HE FOUND A LIMESTONE IN A REASONABLE POSITION** AT THE SOUTHEAST CORNER OF THE WEST 1/2 OF THE SOUTHEAST 1/4 OF SECTION 3-21-11. **HE SET REBARS ALONG SIDE OF THE STONE.**

- 1) 9.6' NE TO A PK NAIL & WASHER IN A FENCE POST
- 2) 4.9' NORTH TO A PK NAIL & WASHER IN A CORNER POST
- 3) 35.5' WEST TO A FENCE POST WITH A WATER LINE SIGN
- 4) IN LINE WITH A FENCE TO THE NORTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,308.52' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 3-21-11
- 2) 1,549.26' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 3) 2,329.26' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 4) 2,629.26' WEST TO THE THEORETICAL POSITION FOR THE SOUTH 1/16TH CORNER OF THE WW1/4 OF SECTION 3-21-11
- 5) 3,179.26' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 6) 3,950.00' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP" HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-21-11
- 7) 2,642.68' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE SE1/4 OF SECTION 3-21-11
- 8) 3,092.68' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTH-EAST CORNER OF TRACT "4
- 9) 5,521.25' NORTH TO THE SPIKE IN ASPHALT HE FOUND AT THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF SECTION 3-21-11
- 10) SURVEY COORDINATES: NORTH = 5771.22 EAST = 6458.40

NORTH SIXTEENTH CORNER NORTHEAST QUARTER 10-21-11