

**WEST 1/16TH CORNER OF THE NORTHWEST QUARTER OF SECTION 10, TOWNSHIP 21 SOUTH, RANGE 11 EAST**

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN SURVEY F10007 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR FOUR TRACTS COMPRISING THE OLPE CITY LAKE, LOCATED IN PARTS OF THE NORTHEAST QUARTER, THE SOUTHEAST QUARTER AND THE SOUTHWEST QUARTER OF SECTION 3, AND PART OF THE NORTHWEST QUARTER OF SECTION 10, ALL IN TOWNSHIP 21, RANGE 11, SAID IN HIS *REPORT OF SURVEY* THAT HE DETERMINED A **THEORETICAL POSITION** FOR THE WEST 1/16<sup>TH</sup> CORNER OF THE NORTHWEST 1/4 OF SECTION 10-21-11 TO BE ON LINE AND HALFWAY BETWEEN THE NORTHWEST CORNER AND THE WEST 1/4 CORNER OF SECTION 10-21-11, BUT THE POSITION WAS **NOT** MONUMENTED ON THIS SURVEY.

**HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**

- 1) 1,319.27' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 10-21-11
- 2) 1,319.27' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE SW1/4 OF SECTION 3-21-11
- 3) 3,957.18' NORTH TO THE GLO SANDSTONE HE FOUND AT THE WEST 1/4 CORNER OF SECTION 3-21-11
- 4) 6,798.72' NORTH TO THE SPIKE IN ASPHALT HE FOUND AT THE NORTHWEST CORNER OF SECTION 3-21-11 ON THE 4<sup>TH</sup> STANDARD PARALLEL
- 5) 1,320.2' EAST TO THE THEORETICAL POSITION FOR THE CENTER CORNER OF THE NW1/4 OF SECTION 10-21-11
- 6) 1,620.2' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 7) 2,020.2' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET
- 8) 2,640.4' EAST TO THE THEORETICAL POSITION FOR THE EAST 1/16<sup>TH</sup> CORNER OF THE NW1/4 OF SECTION 10-21-11

WEST SIXTEENTH CORNER NORTHWEST QUARTER 10-21-11