

NORTH 1/4 CORNER SECTION 11, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 414 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 13" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 11-21-11 .

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.67-1/2* CHAINS WEST TO THE 24" X 14" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-11
- 2) 39.77-1/2 CHAINS EAST TO THE 20" X 19" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-11
- 3) * **NOTE:** THIS IS THE REMAINDER LEFT WHEN THEY RAN THE TRUE LINE WEST OF THE NORTHEAST CORNER OF SECTION 11 AND THEY SET THE 1/4 CORNER AT 39.77-1/2 CHAINS WEST OF THE NORTHEAST CORNER AS NOTED IN THE FIELD NOTES AND ON THE HISTORICAL SOCIETY DISC. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 13, A ROAD SURVEY RECORDED IN ROAD SURVEY BOOK "E" ON PAGE 193 DATED OCTOBER 4, 1900, FOR A ROAD IN TOWNSHIP 21-11 FOR CLEMMENS NUESSEN, PRINCIPAL PETITIONER, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 OF SECTION 2-21-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING DISTANCES:

- 1) 19.85 CHAINS WEST TO THE STONE HE SET FOR THE SOUTH END OF THE LINE BETWEEN THE E1/2 AND THE W1/2 OF THE SW1/4 OF SECTION 2-21-11
- 2) 39.70 CHAINS WEST TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 2-21-11

- 3) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 2002, FOR PROJECT NUMBERS 02448-02, 02121-02, AND 02450-02, SURVEY F02007 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF THREE TRACTS IN FRACTIONAL SECTION 2-21-11, SAID THAT **HE FOUND A 1/2" REBAR IN CONCRETE OF UNCERTAIN ORIGIN** AT THE SOUTH 1/4 CORNER OF SECTION 2-21-11.

- 1) 18.6' SOUTH TO A 40 D SPIKE & WASHER IN A POWER POLE
- 2) 24.15' NNW TO A 40 D SPIKE & WASHER IN A 22" HONEY LOCUST TREE
- 3) 23.80' SW TO A CONCRETE NAIL & SHINER IN A FENCE POST
- 4) IN LINE WITH A HEDGE TO THE NORTH
- 5) IN LINE WITH A TREE ROW TO THE SOUTH
- 6) 4.6' EAST TO A LINE OF FENCE TO THE NORTH
- 7) 1.50' NORTH TO THE CENTERLINE TRAVELED WAY OF GRAVEL COUNTY ROAD 60

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,896.22' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NORTH 20 ACRES OF THE SE1/4 OF SECTION 2-21-11 LYING WEST OF THE RAILROAD
- 2) 2,643.50' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE NE1/4 OF SECTION 2-21-11
- 3) 3,633.50' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE SOUTH 30 ACRES OF THE E1/2 OF THE NW1/4 OF SECTION 2-21-11
- 4) 5,554.45' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHWEST CORNER OF THE NE1/4 OF SECTION 2-21-11 ON THE 4TH STANDARD PARALLEL

HIS INFORMATION IS CONTINUED ON PAGE 2

- 5) 1,683.07' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE P.O.B. OF TRACT 3, BEING IN THE CENTER OF THE AT&SF RAILWAY RIGHT-OF-WAY, NOW ABANDONED
 - 6) 2,614.89' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP IN A DRILL HOLE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 2-21-11
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN THE FINAL PLAT FOR *ANDREA ACRES* IN THE SOUTHEAST 1/4 OF SECTION 2-21-11 DATED DECEMBER 31, 2002 FOR PROJECT NUMBER 02449-02, FILED IN THE LARGE SURVEY DRAWER FOR TOWNSHIPS 20-10 TO 20-13, SHOWS THAT **HE FOUND A 1/2" REBAR** AT THE SOUTHWEST CORNER OF THE SOUTHEAST 1/4 OF SECTION 2-21-11. HIS TIES FROM NOVEMBER 2002 ARE STILL VALID.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,614.89' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP IN A DRILL HOLE HE FOUND AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 2-21-11
- 5) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE DATED MARCH 25, 2009 FOR PROJECT NUMBER 09054-01 AND SURVEY F02008 IN THE SURVEY FILE FOR TOWNSHIP 21-11 FOR THE SURVEY OF A 1.2 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 2-21-11 FOR PHILIP KIMERER, SAID THAT **HE FOUND THE 1/2" REBAR** AT THE SOUTH 1/4 CORNER OF SECTION 2-21-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE.
- 1) 18.60' SOUTH TO A 40 D NAIL & WASHER IN A POWER POLE
 - 2) 24.10' NW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 3) 19.70' NORTH TO A CONCRETE NAIL & WASHER IN A BRACE POST
 - 4) IN LINE WITH A HEDGE TO THE NORTH EXTENDED
 - 5) IN LINE WITH A HEDGE TO THE SOUTH EXTENDED
 - 6) 13.60' WEST TO A LINE OF FENCE TO THE NORTH EXTENDED
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 5,554.12' NORTH TO THE 1/2" REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 2-21-11 ON THE 4TH STANDARD PARALLEL
- 4) STEVEN S. BROSEMER, L.S. 752, IN THE FINAL PLAT FOR *PRAIRIE LAKE ESTATES*, BEING A PART OF THE EAST HALF OF THE SOUTHWEST QUARTER AND THE EAST HALF OF THE NORTHWEST QUARTER OF SECTION 2, TOWNSHIP 19, RANGE 11 FOR TYLER SCHMIDT DATED JUNE 8, 2011, PROJECT NUMBER 10359, LARGE SURVEY NUMBER SR #02005 IN THE SURVEY DRAWER FOR TOWNSHIP 20-11, SHOWS ON HIS PLAT THAT **HE FOUND THE 1/2" REBAR** AT THE SOUTHEAST CORNER OF THE EAST 1/2 OF THE SOUTHWEST 1/4 OF SECTION 2-21-11. HIS TIES ARE MISSING FROM THE SURVEY TIE FILES.
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 1,310.45' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 2-21-11
 - 2) 30' NORTH TO THE 1/2" X 24" REBAR WITH HIS "LS 752" CAP HE SET ON THE NORTH RIGHT-OF-WAY LINE OF COUNTY ROAD 60, BEING THE SOUTHEAST CORNER OF LOT 2 OF BLOCK "B" AND THE SOUTHEAST CORNER OF LOT 3 OF BLOCK "B"
 - 3) 974.67' NORTH TO THE 1/2" X 24" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF LOT 3 OF BLOCK "B" AND THE SOUTHEAST CORNER OF LOT 4 OF BLOCK "B"
 - 4) 1,644.67' NORTH TO THE 1/2" X 24" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF LOT 4 OF BLOCK "B" AND THE SOUTHEAST CORNER OF LOT 5 OF BLOCK "B"

HIS INFORMATION IS CONTINUED ON PAGE 3

- 5) 2,643.21' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE E1/2 OF THE SW1/4 OF SECTION 2-21-11, BEING THE NORTHEAST CORNER OF LOT 6 OF BLOCK "B" AND THE NORTHEAST CORNER OF LOT 5 OF BLOCK "B"

NORTH QUARTER CORNER 11-21-11