

NORTHWEST CORNER SECTION 11, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 414 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 14" X 4"** FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-11.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 27" X 17" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-21-11
- 2) 83.86 CHAINS NORTH TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2 & 3-21-11 ON THE 4TH STANDARD PARALLEL
- 3) 39.67-1/2* CHAINS EAST TO THE 24" X 14" X 3" SANDSTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 11-21-11
- 4) 79.45 CHAINS EAST TO THE 20" X 19" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-11
- 5) * THIS IS THE REMAINDER LEFT WHEN THEY RAN THE TRUE LINE WEST OF THE NORTHEAST CORNER OF SECTION 11-21-11 AND THEY SET THE 1/4 CORNER AT 39.77-1/2 CHAINS WEST OF THE NORTHEAST CORNER – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR

- 2) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 392 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 514 TO 516 PETITIONED BY VALENTINE FREITAG AND OTHERS FOR A ROAD IN TOWNSHIP 21-11 [PACKET 643 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON MAY 24, 1893, WAS ESTABLISHED AS A 50 FOOT AND 80 FOOT WIDE ROAD ON JULY 7, 1893 AS NOTED BY W. N. D. BIRD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON JULY 15, 1893 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 11-21-11 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS EAST ON THE SECTION LINES, TAKING 25 FEET ON EACH SIDE OF THE SECTION LINE, TO A POINT 600 FEET WEST OF THE RIGHT-OF-WAY OF THE A. T. & S. F. RAILROAD, THENCE EAST ON THE SECTION LINE TAKING 40 FEET ON EACH SIDE OF THE SECTION LINE TO THE A. T. & S. F. RAILROAD, THENCE EAST TAKING 25 FEET ON EACH SIDE OF THE SECTION LINE TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 11-21-11 AT THE TERMINUS OF THIS ROAD SURVEY
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 13, A ROAD SURVEY RECORDED IN ROAD SURVEY BOOK "E" ON PAGE 193 DATED OCTOBER 4, 1900, FOR A ROAD IN TOWNSHIP 21-11 FOR CLEMMENS NUESSEN, PRINCIPAL PETITIONER, SHOWS ON HIS SURVEY DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 2-21-11 ON THIS ROAD SURVEY.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 19.85 CHAINS EAST TO THE STONE HE SET AT THE SOUTH END OF THE LINE BETWEEN THE E1/2 AND THE W1/2 OF THE W1/2 OF SECTION 2-21-11
 - 2) 39.70 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 2-21-11
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 13, A ROAD SURVEY RECORDED IN ROAD SURVEY BOOK "E" ON PAGE 193 DATED OCTOBER 4, 1900 FOR A ROAD IN SECTION 2-21-11 FOR CLEMMENS NUESSEN, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 2-21-11 CORNER ON THIS ROAD SURVEY.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) 19.85 CHAINS EAST TO THE STONE HE SET FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 2-21-11
 - 2) 39.70 CHAINS EAST TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 2-21-11
- 5) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 56
 ON JANUARY 15, 1919 A PETITION SIGNED BY A. F. ROSSILLON AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 21-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON FEBRUARY 11, 1919, AND THE FINAL ORDER WAS ISSUED ON MARCH 7, 1919 TO **VACATE** THE FOLLOWING ROAD:
- 1) BEGINNING AT THE WEST LINE OF SECTION 3 AND 10-21-11; THENCE EAST BETWEEN SAID SECTIONS 3 AND 10 ONE MILE AND TERMINATE AT THE EAST LINE OF SECTIONS 3 AND 10.
- 6) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 705 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 62 PETITIONED BY A. F. ROSSILLON AND OTHERS FOR THE **VACATION** OF A ROAD IN TOWNSHIP 21-11 [PACKET 829 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND THE COUNTY SURVEYOR ON FEBRUARY 11, 1919 AND WAS ORDERED THAT THE ROAD BE **VACATED** AS PETITIONED FOR AS THE ROAD IS NOT BEING USED BY THE PUBLIC ON FEBRUARY 11, 1919 AS NOTED BY C. A. PAINE, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS: BEGINNING AT THE WEST LINE OF SECTIONS 3 AND 10, TOWNSHIP 21, RANGE 11, FROM THENCE EAST BETWEEN SAID SECTIONS 3 AND 10 FOR 1 MILE, AND TERMINATING AT THE EAST LINE OF SAID SECTIONS 3 & 10-21-11.
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-11 SHOWS A **STONE** AT THE "SE CORNER SECTION 3-21-11".
- 1) 40' WEST TO AN IRON PIN IN A FENCE
 - 2) 40' NE TO AN IRON PIN
- 8) KRETSINGER REFERENCE TIE BOOK 13 ON PAGE 69 AT THE BOTTOM OF THE PAGE SHOWS A **STONE** AT THE "NW CORNER SECTION 11-21-11".
- 1) 40.0' WEST TO AN IRON PIN IN A FENCE
 - 2) 40.0' NE TO AN IRON PIN IN A ROW OF HEDGE STUMPS
- 9) FIELD BOOK 32 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE ON PAGE 69 SHOWS THE FOLLOWING TIES TO THE **CORNER STONE** AT THE NORTHWEST CORNER OF SECTION 11-21-11. THERE IS NO DATE ON THE PAGE.
- 1) 40.0' WEST TO AN IRON PIN IN A FENCE
 - 2) 40.0' NE TO AN IRON PIN IN A ROW OF HEDGE STUMPS
 - 3) 25.0' NORTH TO A ROW OF HEDGE STUMPS
- 10) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 20, 1989, SURVEY F10007 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR FOUR TRACTS COMPRISING THE OLPE CITY LAKE, LOCATED IN PARTS OF THE NORTHEAST QUARTER, THE SOUTHEAST QUARTER AND THE SOUTHWEST QUARTER OF SECTION 3, AND PART OF THE NORTHWEST QUARTER OF SECTION 10, ALL IN TOWNSHIP 21, RANGE 11, SAID IN HIS *REPORT OF SURVEY* THAT **HE FOUND THE GLO LIMESTONE** AT THE SOUTHEAST CORNER OF SECTION 3-21-11. **HE SET REBARS ON THE EAST AND WEST SIDES OF THE STONE.**
- 1) 40.0' NE TO A SQUARE 1/2" IRON PIN
 - 2) 25.0' NNW TO A PK NAIL & WASHER IN A POWER POLE
 - 3) 20.0' WNW TO A PK NAIL & WASHER IN A POWER POLE

HIS TIES ARE CONTINUED ON PAGE 3

- 4) 21.5' NORTH TO A FENCE LINE TO THE EAST
 - 5) 5.0' NORTH TO A FENCE LINE TO THE WEST [EXTENDED]
- 11) WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 23, 1996, **FOUND THE GLO LIMESTONE WITH THE 1/2" REBARS ON THE EAST AND WEST SIDES OF THE STONE** AT THE NORTHWEST CORNER OF SECTION 11-21-11 FROM REFERENCES IN AI CHAMNESS SURVEY BOOKS ON FILE IN THE COUNTY ENGINEER'S OFFICE, AND STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, TIES OF 1989. THE TOP PIECE OF STONE IS 10" NORTH-SOUTH BY 2.5" EAST-WEST BY 6" TALL AND SETS ON TOP OF THE REST OF THE STONE. **I DRILLED A HOLE IN THE CENTER OF THE TOP PIECE OF THE STONE, AND PUT A PK NAIL IN THE HOLE IN THE STONE** AT THE NORTHWEST CORNER OF SECTION 11-21-11.
- 1) 40.0' NE TO A 1/2" SQUARE REBAR FOUND [AI CHAMNESS REFERENCE] 3.5' NORTH OF AN EAST-WEST FENCE
 - 2) 25.0' NNW TO A PK NAIL & WASHER IN A POWER POLE
 - 3) 20.7' WNW TO A PK NAIL & WASHER IN THE SOUTH GATE POST
 - 4) 23.8' NNW TO A PK NAIL & WASHER IN THE EAST GATE POST
 - 5) IN THE TRAVELED WAY OF COUNTY ROAD "L" TO THE SOUTH—EXTENDED
 - 6) 6' NORTH TO THE TRAVELED WAY OF COUNTY ROAD 60 TO THE EAST—EXTENDED

NORTHWEST CORNER 11-21-11