

NORTH 1/4 CORNER SECTION 12, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 406 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 24" X 8" X 6"** FOR THE 1/4 CORNER BETWEEN SECTIONS 1 & 12-21-11.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.98-1/2 CHAINS WEST TO THE 20" X 19" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 1, 2 11 & 12-21-11
 - 2) 39.98-1/2 CHAINS EAST TO THE 18" X 14" X 6" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 1 & 12-21-11 ON THE EAST TOWNSHIP BOUNDARY

- 2) IN A FIELD BOOK LABELED "1957-1958" STORED IN THE VAULT IN THE COUNTY ENGINEERS OFFICE ON PAGE 48 FOR THE LEVELS OF ARMOUR SHAVER DATED JANUARY 31, 1958, IT SHOWS AN **IRON PIN IN LINE WITH A HEDGE TO THE SOUTH** AT THE NORTH 1/4 CORNER OF SECTION 12-21-11.
 - 1) IN LINE WITH A HEDGE TO THE SOUTH
 - 2) 35' SOUTH TO A STAKE
 - 3) 26.5' NORTH TO THE EAST GATE POST

- 3) FRANKE SINKER, L.S. 1086, KDOT DESIGN SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 7, 2004, FOR PROJECT NUMBER 57-56 K-9654-01, SURVEY F01002 IN THE SURVEY FILE FOR TOWNSHIP 20-11, SAID THAT **HE FOUND A 1/2" SQUARE REBAR AT 0.7 FEET DEEP** AT THE SOUTH 1/4 CORNER OF SECTION 1-21-11. THE MONUMENT WAS RECOVERED USING LYON COUNTY SURVEY NOTES FILED FOR THE NORTH 1/4 CORNER OF SECTION 12-21-11E AND LYON COUNTY FIELD BOOK LABELED "1957-1958" STORED IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE 48 AND DATED 1/31/58. NOTES ON THE BACK OF THE SURVEY REFERENCE REPORT ON THE EXCAVATION SHOWED THAT THEY DUG A HOLE 23.3' N-S BY 10.5' E-W BY 2.5 FEET DEEP. HE SAID THAT BELOW THE GRAVEL ROAD SURFACE, THE DIRT WAS VERY "CLEAN" WITH NO ROCKS OR GRAVEL OF ANY KIND. HE SAID THAT AT ABOUT 2 FEET DEEP THEY HIT YELLOW/BROWN CLAY SUBSOIL. KDOT CORNER NUMBER 18021
 - 1) 34.4' NE TO A SPIKE & KDOT WASHER IN THE TOP OF A WOOD FENCE POST
 - 2) 45.4' SW TO A SPIKE & KDOT WASHER IN THE TOP OF A WOOD FENCE POST
 - 3) 20.2' SOUTH TO A 10 D SPIKE & WASHER IN THE EAST FACE OF A FENCE POST
 - 4) 26.55' NORTH TO A 10 D SPIKE & WASHER IN THE EAST FACE OF THE EAST GATE POST
 - 5) 28.0' SOUTH TO A FENCE TO THE WEST
 - 6) 25.5' NORTH TO AN EAST-WEST FENCE
 - 7) IN LINE WITH A FENCE TO THE SOUTH
 - 8) 2.5' SOUTH TO THE TRAVELED WAY OF THE ROAD
 - 9) 9.5' WEST TO THE TRAVELED WAY OF A FIELD ENTRANCE TO THE NORTHTHE DRAWING SIGNED BY WILLIAM J. HAVERKAMP, R.L.S. 886, DATED JANUARY 6, 2005, SHOWS THE FOLLOWING INFORMATION AND DISTANCES:
 - 1) STATE PLANE COORDINATES NAD 83 [1997 ADJUSTMENT] CAF = 0.999901021
N = 1895589.68 E = 1988188.56
 - 3) 2,638.91' WEST TO THE 1/2" REBAR WITH "LS 752" CAP IN A DRILL HOLE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-21-11
 - 4) 2,641.94' NORTH TO THE 1/2" REBAR WITH A KDOT ALUMINUM CAP HE SET FOR THE CENTER CORNER OF SECTION 1-21-11
 - 5) 2,633.23' EAST TO THE 15" X 11" X 6" SANDSTONE HE FOUND 12" DEEP AT THE SOUTHEAST CORNER OF SECTION 1-21-11 ON THE RANGE LINE

NORTH QUARTER CORNER 12-21-11