

WEST 1/4 CORNER SECTION 14, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 413 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 30" X 12" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 15-21-11.

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 30, 2013 FOR PROJECT NUMBER 13200, THE SURVEY OF AN 11.04 ACRE TRACT IN THE SOUTHEAST 1/4 OF SECTION 15-21-11 FOR STEVE REDEKER, SURVEY F15001 IN THE SURVEY FILE FOR TOWNSHIP 21-11, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 15-21-11 WAS **OBLITERATED** AS THE POSITION FALLS IN A ROAD CUT. **HE SET A 5/8" X 30" IRON PIN WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 15-21-11 IN LINE WITH A FENCE TO THE WEST AND IN THE CENTER OF THE ROAD.
 - 1) 24.9' WEST TO A CONCRETE NAIL & BOTTLECAP IN THE EAST FACE OF A CORNER FENCE POST
 - 2) 21.35' WSW TO THE NEAR FACE OF A FIBER OPTIC SIGN POST AT THE GROUND
 - 3) IN LINE WITH A FENCE TO THE WEST EXTENDED
 - 4) IN LINE WITH THE TRAVELED WAY OF GRAVEL COUNTY ROAD "L" NORTH-SOUTH

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

 - 1) 503.00' SOUTH ON THE SECTION LINE TO THE TRUE POINT OF BEGINNING OF THE 11.04 ACRE TRACT
 - 2) 1,266.00' SOUTH ON THE SECTION LINE TO THE SOUTHEAST CORNER OF THE 11.04 ACRE TRACT
 - 3) 2,632.67' SOUTH ON THE SECTION LINE TO THE 1/2" X 24" IRON PIN WITH HIS "S. BROSEMER" CAP HE SET FOR THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 15-21-11

WEST QUARTER CORNER 14-21-11