

**NORTH 1/4 CORNER SECTION 18, TOWNSHIP 21 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 432 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 15" X 12" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 7 & 18-21-11.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 34.96 CHAINS WEST TO THE 32" X 13" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7 & 18-21-11 ON THE WEST TOWNSHIP BOUNDARY
  - 2) 40.00 CHAINS EAST TO THE 18" X 16" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 7, 8, 17 & 18-21-11
  
- 2) THE FIELD BOOK LABELED "MISC. 1967-1970" STORED IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE, IT SHOWS A **1/2" IRON PIN** AT THE NORTH 1/4 CORNER OF SECTION 18-21-11.
  - 1) 24.7' SOUTH TO A CORNER POST
  - 2) 27.4' NORTH TO A CORNER POST
  
- 3) JAMES H. BROSEMER, L.S. 82, IN A LAND SURVEY REFERENCE REPORT DATED MAY 30, 2001, SURVEY F07001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE WEST FRACTIONAL HALF OF SECTION 7-21-11 FOR CLIFF COLE, SAID IN HIS *REPORT OF SURVEY* THAT HE EXCAVATED FOR THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 7-21-11 WITH A COUNTY BACKHOE, BUT HE DID **NOT** FIND THE STONE. HE CONSIDERED THAT THIS CORNER WAS **LOST. HE SET A 1/2" REBAR WITH HIS "LS 82" CAP** FOR THE SOUTH 1/4 CORNER OF SECTION 7-21-11 ON TRUE LINE AND AT THE GLO PRORATION BETWEEN THE SOUTHWEST CORNER AND THE SOUTHEAST CORNER OF SECTION 7-21-11.
  - 1) 8.5' WEST TO A LINE OF FENCE TO THE NORTH
  - 2) 8.7' EAST TO A LINE OF FENCE TO THE SOUTH
  - 3) 20.0' NORTH TO A 1/2" REBAR WITH HIS "LS 82" CAP SETHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,441.67' WEST TO THE SOUTHEAST CORNER OF TRACT #1, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET AT 20' NORTH ON THE ROAD EASEMENT LINE
  - 2) 1,837.67' WEST TO THE P.O.B. OF TRACT #1, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET AT 20' NORTH ON THE ROAD EASEMENT LINE
  - 3) 2,299.67' WEST TO THE 5/8" REBAR OVER THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 7-21-11
  - 4) 2,638.76' EAST TO THE 5/8" REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 7-21-11
  - 5) 3,959.18' NORTH TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE SOUTHEAST CORNER OF TRACT #2
  - 6) 5,254.18' NORTH TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET ON THE SOUTH ROAD EASEMENT LINE
  - 7) 5,279.18' NORTH TO THE 1/2" REBAR WITH HIS "LS 82" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF SECTION 7-21-11, AND THE NORTHEAST CORNER OF TRACT #2
  
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 01, 2006, FOR PROJECT NUMBER 06144-02, SURVEY F17001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR THE SURVEY OF A 0.45 ACRE TRACT IN THE NORTHWEST QUARTER OF SECTION 17-21-11 FOR LYON COUNTY [HUTH DEED] RIGHT-OF-WAY TRACT, SAID THAT **HE FOUND THE 1/2" REBAR WITH A "LS 82" CAP** AT THE NORTH 1/4 CORNER OF SECTION 18-21-11 FROM EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE FROM JAMES H. BROSEMER, L.S. 82, IN 2001.

HIS TIES ARE ON PAGE 2

- 1) 30.0' NORTH TO A 1/2" REBAR WITH "LS 82" CAP FOUND
- 2) IN LINE WITH A FENCE TO THE NORTH
- 3) IN LINE WITH A FENCE TO THE SOUTH
- 4) 2,638.76' EAST TO A 5/8" REBAR WITH A LYON COUNTY CAP SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 17-21-11

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,638.76' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 17-21-11
- 2) 2,824.36' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 0.45 ACRE TRACT, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 20.00' SOUTH ON THE SOUTH RIGHT-OF-WAY LINE OF COUNTY ROAD 50
- 3) 5,299.49' EAST TO THE RAILROAD SPIKE HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 17-21-11

NORTH QUARTER CORNER 18-21-11