

**WEST 1/4 CORNER SECTION 19, TOWNSHIP 21 SOUTH, RANGE 11 EAST**

- 1) ON PAGE 108 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 14" X 10" X 4"** FOR THE WEST 1/4 CORNER OF SECTION 19-21-11 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 27, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH ON THE WEST TOWNSHIP BOUNDARY TO THE 22" X 15" X 2-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 18 & 19-21-11
- 2) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 20" X 13" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19 & 30-21-11

- 2) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 9

ON NOVEMBER 6, 1911 A PETITION SIGNED BY A. F. ROSSILLON AND OTHERS FOR THE LOCATION AND VACATION OF A ROAD IN TOWNSHIP 21-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON DECEMBER 13, 1911, AND THE FINAL ORDER FOR THE LOCATION AND **VACATION** OF THE FOLLOWING ROAD WAS ISSUED ON JANUARY 5, 1912.

- 1) THE ROAD LOCATED BEGINS AT A POINT ON THE WEST SIDE OF THE PRESENT ROAD BETWEEN SECTION 24-21-10 AND SECTION 19-21-11, ABOUT 50 (FIFTY) RODS SOUTH OF THE NORTHEAST CORNER OF THE SOUTHEAST 1/4 OF SECTION 24-21-10; THENCE IN A SOUTHWESTERLY DIRECTION ACROSS THE CREEK AT THE SITE OF THE NEW BRIDGE AS STAKED TO A POINT BEYOND THE BEND IN THE CREEK; THENCE IN A SOUTHEASTERLY DIRECTION TO THE PRESENT ROAD AND TERMINATION THERE
- 2) SAID LOCATED ROAD TO BE 40 FEET WIDE
- 3) **VACATE** COMMENCING AT THE SOUTH EDGE OF THE BEGINNING OF THE ABOVE ROAD AS DESCRIBED; THENCE SOUTH TO THE NORTH EDGE OF THE ABOVE ROAD AT THE POINT WHERE IT ENTERS THE OLD ROAD AND TERMINATING THERE

- 3) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 12, 2009 FOR PROJECT NUMBER 08192-02, SURVEY F24001 IN THE SURVEY FILE FOR TOWNSHIP 21-10 FOR LYON COUNTY BRIDGE REPLACEMENT PROJECT NUMBER 08-QY FOR THE LYON COUNTY ROAD & BRIDGE DEPARTMENT, SAID THAT HE CONSIDERED THAT THE EAST 1/4 CORNER OF SECTION 24-21-10 ON THE RANGE LINE WAS **LOST**. **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE EAST 1/4 CORNER OF SECTION 24-21-10 BY PROPORTIONATE MEASUREMENT ALONG THE RANGE LINE BETWEEN THE NORTHEAST CORNER OF SECTION 13-21-10 AND THE SOUTHEAST CORNER OF SECTION 24-21-10.

- 1) 82.80' NE TO THE TOP CENTER OF A TELEPHONE PEDESTAL
- 2) 60.75' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 3) 11.45' WSW TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
- 4) 12.0' EAST TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD "G"
- 5) 5.0' SOUTH TO A LINE OF FENCE TO THE WEST EXTENDED
- 6) 28.70' SW TO A 40 D NAIL & WASHER IN THE TOP OF A STEEL FENCE POST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,631.84' SOUTH ON THE RANGE LINE TO THE 1/2" SQUARE REBAR HE FOUND AT THE SOUTHEAST CORNER OF SECTION 24-21-10
- 2) 2,631.84' NORTH ON THE RANGE LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF SECTION 24-21-10
- 3) 7,895.52' NORTH ON THE RANGE LINE TO THE 5/8" REBAR OVER THE STONE HE FOUND AT THE NORTH-EAST CORNER OF SECTION 13-21-10
- 4) SURVEY COORDINATES: NORTH = 14,361.459 EAST = 10,048.070

WEST QUARTER CORNER 19-21-11