

NORTH 1/4 CORNER SECTION 20, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 430 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 17 & 20-21-11.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.19-1/2 CHAINS WEST TO THE 21" X 12" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 17, 18, 19 & 20-21-11
 - 2) 40.19-1/2 CHAINS EAST TO THE 27" X 13" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-21-11

- 2) A. J. BAKER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 23, A **CONSENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 23 DATED APRIL 8, 1884 TO ESTABLISH THE NORTH 1/4 CORNER, CENTER CORNER, AND THE SOUTHWEST AND SOUTHEAST CORNERS OF THE OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 17-21-11 BY THE CONSENT OF ALL PARTIES INTERESTED, JAMES YORK, J. H. DUNAGAN, AND F. E. SMITH, SAID THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 17-21-11 ON THIS **CONSENT SURVEY**.

NORTH QUARTER CORNER 20-21-11