

CENTER CORNER OF SECTION 21, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED DECEMBER 06, 1995, FOR PROJECT NUMBER 95005-02, SURVEY F21001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 TO SURVEY THE NORTH AND SOUTH HALVES OF THE NORTHWEST QUARTER OF SECTION 21-21-11, SAID THAT **HE SET A 5/8" REBAR WITH A LYON COUNTY CAP** FOR THE CENTER OF SECTION 21 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE QUARTER CORNERS. SEE THE SURVEY FILED IN VOLUME 495 ON PAGE 103 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 6, 1995.
 - 1) 1.9' WEST TO A 40 D SPIKE & WASHER IN A 12" DIAMETER HONEY LOCUST TREE
 - 2) 2.0' WEST TO AN EXTENSION OF A HEDGE LINE TO THE NORTH
 - 3) 7.0' WEST TO A WIRE FENCE RUNNING NORTH & SOUTH
 - 4) 9.0' NORTH TO A 40 D SPIKE & WASHER IN AN 8" HACKBERRY TREE
 - 5) 11.5' SOUTH TO A CONCRETE NAIL & WASHER IN THE WEST SIDE OF A 40" HEDGE TREE
 - 6) 11.0' SOUTH TO A WIRE FENCE TO THE WEST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING DISTANCES:**
- 1) 2,642.57' WEST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE WEST 1/4 CORNER OF SECTION 21
 - 2) 1,317.84' NORTH TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTH-EAST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 21
 - 3) 2,635.68' NORTH TO THE GLO LIMESTONE FOUND AT THE NORTH 1/4 CORNER OF SECTION 21
 - 4) 2,645.86' EAST TO A 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE EAST 1/4 CORNER OF SECTION 21
 - 5) 2,636.02' SOUTH TO A 1/2" REBAR FOUND AT THE SOUTH 1/4 CORNER OF SECTION 21 AND REPLACED WITH A 1/2" REBAR WITH HIS "LS 752" CAP

CENTER CORNER 21-21-11