

NORTHWEST CORNER SECTION 21, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 422 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 27" X 13" X 4"** FOR THE CORNER TO SECTIONS 16, 17, 20 & 21-20-11 ON NOVEMBER 29, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS SOUTH TO THE 19" X 14" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 21-21-11
 - 2) 80.00 CHAINS SOUTH TO THE 24" X 12" X 4" SANDSTONE THEY SET FOR THE CORNER TO SECTIONS 20, 21, 28 & 29-21-11
 - 3) 40.10-1/2 CHAINS EAST TO THE 20" X 12" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 16 & 21-21-11
 - 4) 80.21 CHAINS EAST TO THE 24" X 12" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 15, 16, 21 & 22-21-11
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT SIDE OF PAGE 187 DATED AUGUST 26, 1880, FOR A COUNTY ROAD IN TOWNSHIP 21-11, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 16-21-11 ON THIS ROAD SURVEY.

THE ROAD IS DESCRIBED AS FOLLOWS:

- 1) COMMENCING AT THE SOUTHWEST CORNER OF SECTION 33-21-11; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 28; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 21; THENCE NORTH 43 CHAINS; THENCE WEST 38 LINKS TO AN ANGLE; THENCE NORTH 3 CHAINS; THENCE N. 30° E. 7 CHAINS; THENCE N. 10° W. 13 CHAINS; THENCE NORTH ON THE SECTION LINE 15.57 CHAINS TO THE SOUTHWEST CORNER OF SECTION 16; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 9; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 4; THENCE NORTH 82.86 CHAINS TO THE NORTHWEST CORNER OF SECTION 4-21-11 [ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY]
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 87 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 350 TO PETITION BY DANIEL REED AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-13 [PACKET 226 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 26, 1880, WAS ESTABLISHED ON OCTOBER 5, 1880 AS NOTED B I. A. TAYLOR, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON NOVEMBER 15, 1880 BY WILLIAM F. EWING, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE SOUTHWEST CORNER OF SECTION 16-21-11 ON THIS ROAD SURVEY.

THE ROAD IS DESCRIBED AS FOLLOWS:

- 1) COMMENCING AT THE SOUTHWEST CORNER OF SECTION THIRTY-THREE (33), TOWNSHIP TWENTY-ONE (21), RANGE ELEVEN (1) EAST; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 28; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 21; THENCE NORTH 43 CHAINS; THENCE WEST 38 LINKS TO AN ANGLE; THENCE NORTH 3 CHAINS TO AN ANGLE; THENCE N. 30° E. 7 CHAINS TO AN ANGLE; THENCE N. 12° W. 13 CHAINS TO AN ANGLE ON THE SECTION LINE; THENCE NORTH ON THE SECTION LINE 15.57 CHAINS TO THE SOUTHWEST CORNER OF SECTION 16; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 9; THENCE NORTH 1 MILE TO THE SOUTHWEST CORNER OF SECTION 4; THENCE NORTH 82.86 CHAINS TO THE NORTHWEST CORNER OF SECTION 4-21-11 [ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY]. TOTAL LENGTH 6 MILES AND 19-1/4 RODS.

THE INFORMATION IS CONTINUED ON PAGE 2

- 2) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD AS THE PUBLIC CONVEYANCE REQUIRES SAID ROAD TO BE LOCATED FOR PUBLIC TRAVEL.
 - 3) THE VIEWERS DETERMINED THAT IF SAID ROAD BE ESTABLISHED THAT ITS WIDTH SHALL BE FIFTY FEET.
- 4) A. J. BAKER, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 23, IN SURVEY NUMBER TWENTY-THREE, A CONSENT SURVEY RECORDED IN SURVEY BOOK "E" ON PAGE 23 DATED APRIL 8, 1884 TO ESTABLISH THE NORTH 1/4 CORNER, CENTER CORNER, AND THE SOUTHWEST AND SOUTHEAST CORNERS OF THE OF THE NORTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 17-21-11 BY THE CONSENT OF ALL PARTIES INTERESTED, JAMES YORK, J. H. DUNAGAN, AND F. E. SMITH, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 17-21-11 ON THIS CONSENT SURVEY. HE NOTED THAT THE VARIANCE OF THE EAST AND WEST LINES WERE 9°42' AND THE SOUTH LINE 9°17'. THIS CORNER IS THE SOUTHEAST CORNER OF THE F. E. SMITH TRACT.
- 5) NATHANIEL BROWN, DEPUTY COUNTY SURVEYOR, IN A ROAD SURVEY FOR ROAD NUMBER 380 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 466 TO 468 [PACKET 627 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY CLARK JOHNSON AND OTHERS FOR THE LOCATION OF A ROAD IN TOWNSHIPS 21-10 AND 21-11 THAT HE SURVEYED ON SEPTEMBER 9, 1891, WAS ESTABLISHED ON OCTOBER 7, 1891 AS NOTED BY J. W. LAY, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON DECEMBER 30, 1891 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE "PROPERLY MARKED"** AT THE NORTHWEST CORNER OF SECTION 21-21-11 ON THIS ROAD SURVEY. HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:
- 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION 23, TOWNSHIP 21, RANGE 11; THEN WEST 3 MILES; THEN SKIPPING ONE MILE; THEN WEST 1-3/4 MILES TO THE TERMINUS OF THIS ROAD SURVEY. STONES WERE SET AT EACH MILE AND AT THE TERMINUS OF THE ROAD. THE ROAD WAS LAID 20 FEET ON EACH SIDE OF THE SECTION LINE. TOTAL LENGTH 4-3/4 MILES PER GOVERNMENT SURVEY. EXTREME WIDTH 40 FEET.
 - 2) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD AS THEY CONSIDERED IT A PUBLIC CONVENIENCE.
 - 3) THE VIEWERS DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE FORTY (40) FEET.
- 6) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 389 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 502 TO 504 [PACKET 644 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY CLARK JOHNSON AND OTHERS FOR A ROAD IN TOWNSHIPS 21-10 AND 21-11 THAT HE SURVEYED ON MARCH 22, 1893, WAS ESTABLISHED ON APRIL 14, 1893 AS NOTED BY W. N. D. BIRD, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON APRIL 19, 1893 BY C. W. WILHITE, COUNTY CLERK, SAID THAT **HE SET A ROAD STONE** AT THE NORTHWEST CORNER OF SECTION 21-21-11 ON THIS ROAD SURVEY. A NOTE ON THE PACKET COVER SAID TO SEE COMMISSIONERS JOURNAL VOLUME 5 ON PAGE 344. HIS FIELD NOTES AND PLAT SHOWS THE FOLLOWING INFORMATION:
- 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION OF SECTION 23, TOWNSHIP 21, RANGE 11, HENCE RAN WEST ON THE SECTION LINES TO THE NORTHWEST CORNER OF THE EAST HALF OF THE NORTHWEST QUARTER OF SECTION 24, TOWNSHIP 21, RANGE 10, BEING A DISTANCE OF 5-3/4 MILES PER GOVERNMENT SURVEY.
 - 2) ROAD STONES WERE SET AT THE BEGINNING AND TERMINUS OF ROAD, AND AT EACH MILE PER GOVERNMENT SURVEY.

- 3) THE VIEWERS REPORTED IN FAVOR OF LOCATING SAID ROAD AS A GOOD ROAD CAN BE MADE AT A REASONABLE EXPENSE AND IT WOULD BE OF PUBLIC CONVENIENCE ALSO IT CONNECTS EAST AND WEST ROADS.
 - 4) THE VIEWERS DETERMINED THAT IF SAID ROAD BE LOCATED THAT ITS WIDTH SHALL BE 40 (FORTY) FEET.
- 7) MATTHEW BROWN, COUNTY SURVEYOR FROM 1888 TO 1900, AND 1914, IN A ROAD SURVEY FOR ROAD NUMBER 424 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 598 TO 600 [PACKET 6 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY D. J. MARTIN AND OTHERS FOR THE VACATION AND RELOCATION OF ROADS IN TOWNSHIP 21-11 THAT HE SURVEYED ON MAY 21, 1895, WAS ESTABLISHED ON OCTOBER 10, 1895 AS NOTED BY JACOB JACOB, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS AND ATTESTED BY C. W. WILHITE, COUNTY CLERK, AND RECORDED ON OCTOBER 31, 1895 BY MATTHEW BROWN, COUNTY SURVEYOR, VACATED THE ROAD AS PETITIONED: VACATE AT THE SOUTHEAST CORNER OF SECTION 17, TOWNSHIP 21, RANGE 11, THENCE WEST ONE (1) MILE TO THE SOUTHWEST CORNER OF SAID SECTION, TOWNSHIP AND RANGE.
- 8) COMMISSIONER'S ROAD JOURNAL BOOK "A", PAGE 96 IN THE COUNTY CLERK'S OFFICE:
ON DECEMBER 11, 1926 A PETITION SIGNED BY E. M. MURPHY AND OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 21-11 WAS PRESENTED TO THE BOARD OF COUNTY COMMISSIONERS. THE ROAD WAS VIEWED ON JANUARY 11, 1927, AND THE FINAL ORDER WAS ISSUED ON FEBRUARY 11, 1927 TO VACATE THE FOLLOWING ROAD:
- 1) BEGINNING AT THE SOUTHWEST CORNER OF SECTION 17 AND THE NORTHWEST CORNER OF SECTION 20, TOWNSHIP 21, RANGE 11; THENCE EAST TO THE SOUTHEAST CORNER OF SAID SECTION 17 AND THE NORTHEAST CORNER OF SAID SECTION 20, AND THERE ENDING.
- 9) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A ROAD SURVEY FOR ROAD NUMBER 725 RECORDED IN ROAD RECORD BOOK "E" ON PAGE 83 PETITIONED BY E. M. MURPHY AND OTHERS TO VACATE A ROAD IN TOWNSHIP 21-11 THAT WAS VIEWED BY THE COUNTY COMMISSIONERS AND COUNTY SURVEYOR ON JANUARY 10, 1927, AND WAS RECOMMENDED BY THE VIEWERS THAT THE ROAD SHOULD BE VACATED AS PETITIONED FOR AS THERE IS NO DEMAND FOR ROAD AT THIS LOCATION AND IT APPEARS THE ALL THOSE IN THE VICINITY ARE FAVORABLE TO SUCH VACATION AS NOTED BY FRED FOWLER, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS.
THE FOLLOWING ROAD WAS VACATED:
- 1) BEGINNING AT THE SOUTHWEST CORNER OF SECTION 17 AND THE NORTHWEST CORNER OF SECTION 20, TOWNSHIP 21, RANGE 11; THEN EAST ONE MILE TO THE SOUTHEAST CORNER OF SECTION 17 AND THE NORTHEAST CORNER OF SECTION 20-12-11.
- 10) COMMISSIONER'S ROAD JOURNAL BOOK "B", PAGE 27 IN THE COUNTY CLERK'S OFFICE:
ON SEPTEMBER 19, 1944 A PETITION SIGNED BY BUDD LANTZ AND 15 OTHERS FOR THE VACATION OF A ROAD IN TOWNSHIP 21-11 WAS PRESENTED TO GEORGE K. JACKSON, COUNTY CLERK. THE ROAD WAS VIEWED BY THE COUNTY COMMISSIONERS AND E. C. GOLDSMITH, COUNTY ENGINEER, ON OCTOBER 23, 1944 AND THE FINAL ORDER OF THE BOARD OF COUNTY COMMISSIONERS ON OCTOBER 28, 1944 VACATED THE FOLLOWING ROAD:
- 1) BEGINNING AT THE NORTHEAST CORNER OF SECTION 21, TOWNSHIP 21, RANGE 11, THENCE RUNNING WEST ONE (1) MILE TO THE NORTHWEST CORNER OF SECTION 21-21-11 AND THERE ENDING

- 2) THE VIEWERS REPORTED THAT SAID ROAD SHOULD BE **VACATED**. THIS ROAD BEGINNING AT THE NORTHEAST CORNER OF SECTION 21, TOWNSHIP 21 SOUTH, RANGE 11 EAST OF THE 6TH PRINCIPAL MERIDIAN IN LYON COUNTY, THENCE RUNNING WEST ONE (1) MILE TO THE NORTHWEST CORNER OF SAID SECTION, HAS NOT BEEN USED FOR SEVERAL YEARS AND IS NOT NECESSARY TO THE PUBLIC CONVENIENCE, AND THIS BOARD RECOMMENDS THAT THE ROAD BE **VACATED** AS PETITIONED.
 - 3) THE TOWNSHIP TRUSTEE WAS DIRECTED TO CAUSE THE ROAD TO BE **VACATED** FOR PUBLIC TRAVEL.
- 11) THE KRETSINGER REFERENCE TIE BOOKS FOR TOWNSHIP 21-11 SHOWS A **STONE** AT THE "SE CORNER SECTION 17-21-11". THERE ARE NO TIES ON THE PAGE.
 - 12) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-11 SHOWS A **STONE** AT THE "NE CORNER SECTION 20-21-11". BUT THERE ARE NO TIES ON THE PAGE.
 - 13) FIELD BOOK 35 IN THE VAULT IN THE COUNTY ENGINEERS OFFICE ON PAGE 46 SHOWS THE FOLLOWING TIES TO THE SOUTHEAST CORNER OF SECTION 16-21-11 DATED APRIL 27, 1945 TO STAKE THE FENCE LINE IN THE VACATED ROAD ON THE SOUTH SIDE OF SECTION 16-21-11. **THEY NOTED:** "**SET IRON PIN FOR SOUTHWEST CORNER OF SECTION 16-21-11. FOUND ORIGINAL STONE LYING ALONG THE ROAD DITCH**".
THE NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,646.9' EAST TO THE STONE THEY FOUND AT THE SOUTH 1/4 CORNER OF SECTION 16-21-11, IN LINE WITH AN OLD HEDGE FENCE RUNNING SOUTH
 - 2) 5,293.8' EAST TO THE IRON PIN THEY PLACED 6" BELOW THE SURFACE FOR THE SOUTHEAST CORNER OF SECTION 16-21-11 FROM REFERENCES IN BOOK #13.
 - 14) LLOYD J. DOBLER, L.S. 541, IN SURVEY F16001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 FOR A SURVEY OF THE SOUTHWEST QUARTER OF THE SOUTHWEST QUARTER OF SECTION 16-21-11 FOR LARRY REDEKER DATED JUNE 1978, SHOWS ON HIS SURVEY DRAWING THAT HE FOUND A "**MONUMENT**" AT THE SOUTHWEST CORNER OF THE SOUTHWEST 1/4 OF SECTION 16-21-11. **[NOTE:** THERE IS NO DESCRIPTION OF THE "MONUMENT" THAT HE FOUND AND THERE ARE NO TIES ON THE SURVEY OR IN THE SURVEY TIE FILES. WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320.06' NORTH TO THE "PIN SET" FOR THE WEST 1/16TH CORNER OF THE SW1/4 OF SECTION 16-21-11
 - 2) 2,640.12' NORTH TO THE "MONUMENT" AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 16-21-11 – NOT DESCRIBED
 - 3) 1,322.05' EAST TO THE "PIN SET" FOR THE SOUTH 1/16TH CORNER OF THE SW1/4 OF SECTION 16-21-11
 - 15) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 6, 1995, FOR PROJECT NUMBER 95005-02, SURVEY F21001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 TO SURVEY THE NORTH AND SOUTH HALVES OF THE NORTHWEST QUARTER OF SECTION 21-21-11, SAID THAT **HE FOUND THE EXISTING 13" X 4" GLO LIMESTONE** AT THE NORTHWEST CORNER OF SECTION 21-21-11. **HE SET A 5/8" REBAR BENT OVER THE TOP OF THE STONE.** SEE THE SURVEY FILED IN VOLUME 495 ON PAGE 103 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 6, 1995.

HIS TIES ARE ON PAGE 5

- 1) 1.6' WEST TO THE CENTERLINE TRAVELED WAY OF THE COUNTY ROAD RUNNING NORTH-SOUTH
- 2) 24.4' EAST TO THE CENTER OF A CORNER POST OF FENCES RUNNING N-S-E
- 3) 24.6' WEST TO THE CENTER OF A CORNER POST OF FENCES RUNNING N-S-W
- 4) 25.3' ENE TO A CONCRETE NAIL IN A 3.5' CIRCUMFERENCE ELM TREE
- 5) 53.3' SW TO A NAIL & WASHER IN A POWER POLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,645.51' EAST TO THE GLO LIMESTONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 21-21-11
- 2) 5,293.12' EAST TO THE GLO LIMESTONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 21-21-11
- 3) 1,315.67' SOUTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 21-21-11, AS WITNESSED BY A 1/2" REBAR WITH HIS "LS 752" CAP HE SET AT 110.00' EAST DUE TO A CREEK
- 4) 2,631.34' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE WEST 1/4 CORNER OF SECTION 21-21-11
- 5) 5,262.69' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-21-11

- 16) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED SEPTEMBER 13, 2015 FOR PROJECT 15192, THE SURVEY OF A 5 ACRE TRACT IN THE SOUTHWEST 1/4 OF SECTION 16-21-11 FOR YOUNG, SURVEY F16002 IN THE SURVEY FILE FOR TOWNSHIP 21-11, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" IRON PIN WITH A LYON COUNTY CAP BENT OVER THE 13" X 4" GLO LIMESTONE** AT THE SOUTHWEST CORNER OF SECTION 16-21-11 FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY SURVEYORS OFFICE FROM HIS PROJECT 95005 IN 1995.

- 1) 24.45' WEST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
- 2) 23.5' EAST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE GATE POST
- 3) 52.4' SW TO A 40 D NAIL & WASHER IN A POWER POLE
- 4) IN LIEN WITH A FENCE EAST-WEST EXTENDED
- 5) IN THE TRAVELED WAY OF GRAVEL ROAD NORTH-SOUTH [COUNTY ROAD "J"]

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,094.85' NORTH TO THE SOUTHWEST CORNER OF THE 5 ACRE TRACT AS WITNESSED BY THE 1/2" X 24" IRON PIN WITH HIS "PS 752" CAP HE SET AT 25.00' EAST ON THE EAST RIGHT-OF-WAY LINE OF COUNTY ROAD "J"
- 2) 2,639.85' NORTH TO THE 1/2" IRON PIN HE FOUND AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 16-21-11, AND THE P.O.B. OF THE 5 ACRE TRACT

- 17) STEVEN S. BROSEMER, P.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 18, 2016 FOR PROJECT NUMBER 16261-02, THE SURVEY MARKING THE SOUTH LINE OF THE NORTHEAST QUARTER (NE1/4) OF THE SOUTHWEST QUARTER (SW1/4), AND THE SOUTH LINE OF THE NORTH HALF (N1/2) OF THE SOUTHEAST QUARTER (SE1/4) IN SECTION 16, TOWNSHIP 21 SOUTH, RANGE 11 EAST OF THE 6TH P.M. IN LYON COUNTY, KANSAS FOR DAVID ZELLER, SURVEY F16003 IN THE SURVEY FILE FOR TOWNSHIP 21-11, SAID THAT **HE FOUND THE EXISTING RECORD 5/8" IRON PIN WITH A LYON COUNTY CAP BENT OVER THE [13" X 4" GLO] LIMESTONE** AT THE SOUTHWEST CORNER OF SECTION 16-21-11 FROM HIS EXISTING REFERENCE TIES IN 2015 FOR PROJECT NUMBER 15192-02.

- 1) 24.45' WEST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
- 2) 23.5' EAST TO A CONCRETE NAIL & BOTTLECAP IN A CORNER FENCE POST
- 3) 54.2' W TO A 40 D NAIL & WASHER IN A POWER POLE
- 4) IN LINE WITH THE FENCE EAST AND WEST EXTENDED
- 5) IN THE TRAVELED WAY OF GRAVEL COUNTY ROAD "J" NORTH-SOUTH

HIS INFORMATION IS CONTINUED ON PAGE 6

HIS REPORT OF SURVEY SHOWS THE FOLLOWING INFORMATION:

- 1) 1,319.32' NORTH TO THE 1/2" IRON BAR THAT HE FOUND FROM REFERENCE TIES [DOBLER 1978] AT THE NORTHWEST CORNER OF THE SW1/4 OF THE SW1/4 OF SECTION 16-21-11
- 2) 2,639.80' NORTH TO THE 1/2" IRON BAR THAT HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE SW1/4 OF SECTION 16-21-11
- 3) 5,274.32' NORTH TO THE 5/8" IRON BAR THAT HE FOUND FROM REFERENCE TIES AT THE NORTHWEST CORNER OF THE NW1/4 OF SECTION 16-21-11
- 4) 1,322.65' EAST TO THE "POSITION DETERMINED NOT MONUMENTED" FOR THE SOUTHWEST CORNER OF THE SE1/4 OF THE SW1/4 OF SECTION 16-21-11
- 5) 2,645.31' EAST TO THE 1/2" X 24" IRON BAR WITH HIS "PS 752 S. BROSEMER" CAP THAT HE SET FOR THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 16-21-11
- 6) 5,292.66' EAST TO THE STONE THAT HE FOUND FROM REFERENCE TIES AT THE SOUTHEAST CORNER OF THE SE1/4 OF SECTION 16-21-11

NORTHWEST CORNER 21-21-11