

WEST 1/4 CORNER SECTION 21, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 422 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 19" X 14" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 20 & 21-21-11.
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED DECEMBER 6, 1995, FOR PROJECT NUMBER 95005-02, SURVEY F21001 IN THE SURVEY FILE FOR TOWNSHIP 20-11 TO SURVEY THE NORTH AND SOUTH HALVES OF THE NORTHWEST QUARTER OF SECTION 21-21-11, SAID THAT HE DEEMED THAT THE WEST 1/4 CORNER OF SECTION 21-21-11 WAS **LOST. HE SET A 1/2" REBAR WITH HIS "LS 752" CAP** FOR THE WEST 1/4 CORNER OF SECTION 21-21-11 ON LINE AND HALFWAY BETWEEN THE NORTHWEST AND SOUTHWEST CORNERS OF SECTION 21-21-11. SEE THE SURVEY FILED WAS VOLUME 495 ON PAGE 103 IN THE REGISTER OF DEEDS OFFICE ON DECEMBER 6, 1995.
 - 1) 1.5' EAST TO THE CENTERLINE OF TRAVELED WAY OF THE COUNTY ROAD RUNNING NORTH-SOUTH
 - 2) 21.8' EAST TO A FENCE LINE RUNNING NORTH AND SOUTH
 - 3) 19.4' WEST TO A CORNER FENCE POST OF FENCES NORTH-SOUTH-WEST
 - 4) 23.5' NE TO A NAIL & SHINER IN A 9.7" CIRCUMFERENCE WHITE OAK TREE
 - 5) 49.7' NORTH TO THE CENTERLINE OF A 52" DIAMETER CORRUGATED METAL PIPE CULVERT

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,631.35' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTHWEST CORNER OF SECTION 21-21-11
- 2) 1,315.67' NORTH TO THE THEORETICAL POSITION FOR THE NORTHWEST CORNER OF THE S1/2 OF THE NW1/4 OF SECTION 21-21-11, AS WITNESSED BY THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET 110.00' EAST DUE TO A CREEK
- 3) 2,631.34' NORTH TO THE GLO LIMESTONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 21-21-11
- 4) 2,644.57' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 21-21-11
- 5) 5,288.43' EAST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE EAST 1/4 CORNER OF SECTION 21-21-11

WEST QUARTER CORNER 21-21-11