

NORTH 1/4 CORNER SECTION 23, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 413 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A SANDSTONE 24" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 14 & 23-21-11.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 39.90 CHAINS WEST TO THE 19" X 12" X 3-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 14, 1, 22 & 23-21-11
 - 2) 39.90 CHAINS EAST TO THE 29" X 18" X 4-1/2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 13, 14, 23 & 24-21-11

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MARCH 10, 2006, FOR PROJECT NUMBER 06002-02, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE NORTH 1/4 CORNER OF SECTION 23-21-11. **HE FOUND THE 3" X 12" X 24" GLO SANDSTONE** AT THE NORTH 1/4 CORNER OF SECTION 23-21-11.
 - 1) 5/8" X 24" REBAR WITH A LYON COUNTY CAP SET ON THE NORTH SIDE CENTER OF THE STONE
 - 2) 1/2" X 24" REBAR WITH HIS "LS 752" CAP SET ON THE SOUTH SIDE CENTER OF THE STONE
 - 3) 40.10' SE TO A CONCRETE NAIL & WASHER IN A HEDGE POST
 - 4) 27.05' SOUTH TO A CONCRETE NAIL & WASHER IN A CORNER POST
 - 5) 18.25' NORTH TO A CONCRETE NAIL & WASHER IN A CORNER POST
 - 6) IN LINE WITH A FENCE TO THE NORTH AND SOUTH—EXTENDED
 - 7) 3.5' SOUTH TO THE CENTERLINE TRAVELED WAY OF EAST-WEST GRAVEL COUNTY ROAD 40

NORTH QUARTER CORNER 23-21-11