

SOUTH 1/4 CORNER SECTION 34, TOWNSHIP 21 SOUTH, RANGE 11 EAST

- 1) ON PAGE 106 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 14" X 2"** FOR THE SOUTH 1/4 CORNER OF SECTION 34-21-11 ON THE TOWNSHIP LINE AND THE COUNTY LINE ON NOVEMBER 26, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 24" X 18" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 33 & 34-21-11
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 16" X 10" X 5" LIMESTONE SET FOR THE CORNER TO SECTIONS 34 & 35-21-11
- 2) W. G. RUGGLES, COUNTY ENGINEER FROM 1915 TO 1928, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "D" ON PAGE 186 DATED OCTOBER 20-22, 1926 ORDERED BY NELL MARTINDALE, JESSIE MARTINDALE STUGARD, AND HEATH MARTIN TO SURVEY THE JENNIE MARTINDALE ESTATE IN THE NORTHWEST 1/4 OF SECTION 27-2-11, SHOWS ON HIS DRAWING THAT **HE FOUND THE STONE IN PLACE** AT THE SOUTH 1/4 CORNER OF SECTION 34-21-11 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE ON THIS **PERMANENT SURVEY**. THE SURVEY NOTES WERE NOT COMPLETED ON THIS **PERMANENT SURVEY**.
- 3) STATE HIGHWAY COMMISSION SURVEYORS J. L. DOLE & C.A. MARLATTE IN 1930 HAD TO REWORK THE 1929 SURVEY BY OAKES, AND THEY SAID THAT **THEY FOUND A LARGE LIMESTONE** AT THE SOUTH 1/4 CORNER OF SECTION 34-21-11 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE. A COPY OF THEIR FIELD NOTES IS IN THE SURVEY FILE FOR TOWNSHIP 20-11 ON PAGE 17 OF THE NOTES MARKED "KDOT 2".
 - 1) 26.0' SOUTH TO A SPIKE IN A CORNER FENCE POST
 - 2) 33.2' SW TO A SPIKE IN A FENCE POST
 - 3) 27.0' NORTH TO A SPIKE IN A TELEPHONE POLE
- 4) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-11 SHOWS A **STONE** AT THE "S1/4 CORNER SECTION 34-21-11" ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE.
 - 1) 26' SOUTH TO A SPIKE IN A CORNER FENCE POST
 - 2) 33.2' SW TO A SPIKE IN A FENCE POST
 - 3) 27' NORTH TO A SPIKE IN A TELEPHONE POLE
- 5) KRETSINGER REFERENCE TIE BOOK 13 ON A FOLDED OUT SHEET STAPLED TO THE LAST PAGE OF THE BOOK AND LABELED "SECTION CORNERS IN TOWNSHIP 21 S, R 11 E"; IT SHOWS A **LIMESTONE** AT THE "S1/4 CORNER SECTION 34-21-11" ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE.
 - 1) 26.0' SOUTH TO A SPIKE IN A CORNER FENCE POST
 - 2) 33.2' SW TO A SPIKE IN A FENCE POST
 - 3) 27.0' NORTH TO A SPIKE IN A TELEPHONE POLE
- 6) AARON C. DAVIS, L.S. 1368, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED OCTOBER 1, 2010 FOR PROJECT NUMBER 10252-02, SURVEY F33001 IN THE SURVEY FILE FOR TOWNSHIP 21-11 AND LYON COUNTY PROJECT 10-WX SAID THAT HE FOUND A BENT 5/8" REBAR AT THE SOUTH 1/4 CORNER OF SECTION 34-21-11 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE. HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AND **HE FOUND A FRACTURED 6" X 6" LIMESTONE** ON THE SOUTH SIDE OF THE REBAR. HE REMOVED THE BENT 5/8" REBAR AND **HE SET A 5/8" X 30" REBAR WITH A LYON COUNTY CAP THROUGH THE FRACTURED HALVES OF**

THE LIMESTONE AT THE SOUTH 1/4 CORNER OF SECTION 34-21-11 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE.

- 1) 1.5' NORTH TO THE CENTERLINE TRAVELED WAY OF ROAD 10 EAST-WEST
- 2) IN LINE WITH A FENCE TO THE NORTH EXTENDED
- 3) 34.0' NW TO A CONCRETE NAIL & BOTTLECAP IN THE WEST GATE POST
- 4) 28.8' NORTH TO A CONCRETE NAIL & BOTTLECAP IN A CORNER POST
- 5) 30.75' NE TO A CONCRETE NAIL & BOTTLECAP IN THE EAST GATE POST
- 6) 30.0' SOUTH TO A CONCRETE NAIL & BOTTLECAP IN A CORNER POST

HIS DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2,631.87' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHEAST CORNER OF SECTION 33-21-11, AT PROJECT STATION 26+31.87
- 2) 3,663.27' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 1/2" REBAR WITH GEOTECH CAP HE SET FOR P.O.T. STATION 16+00.47
- 3) 3,947.36' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE AXLE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF THE SE1/4 OF SECTION 33-21-11, FROM A PERMANENT SURVEY BY HUNTINGTON, GREENWOOD COUNTY SURVEYOR, DATED APRIL 2, 1930 AND RECORDED AS SURVEY #622 IN SURVEY BOOK "E" AT PAGE 225 IN THE GREENWOOD COUNTY REGISTER OF DEEDS OFFICE, LOCATED 0.28' LEFT OF BASELINE STATION 13+16.38
- 4) 4,263.27' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 1/2" REBAR WITH GEOTECH CAP HE SET FOR P.O.T. STATION 10+00.47
- 5) 5,263.74' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 33-21-11, AT P.O.T. STATION 0+00.00
- 6) SURVEY COORDINATES: NORTH = 0.00 EAST = 5,263.74

SOUTH QUARTER CORNER 34-21-11