

CENTER 1/4 CORNER SECTION 01, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 57 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 114 DATED JANUARY 14, 1875 TO ESTABLISH THE 1/4 CORNER ON THE EAST BOUNDARY AND THE CENTER CORNER OF SECTION 1-21-12, SAID THAT **HE SET A POST** FOR THE PERMANENT CENTER CORNER OF SECTION 1-21-12 ON LINE BETWEEN THE STONE THAT HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 1-21-12 AND THE POST THAT HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 1-21-12 ON THE 4TH STANDARD PARALLEL AND AT 2,640' NORTH OF THE SOUTH 1/4 CORNER OF SECTION 1-21-12 ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 2640' SOUTH TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 1-21-12
 - 2) 3006' NORTH TO THE POST HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 1-21-12 ON THE 4TH STANDARD PARALLEL
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED MAY 13, 2005, FOR PROJECT NUMBER 05129-02, SURVEY F01002 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR A SURVEY TO MARK THE EXTERIOR OF SECTION 1-21-12 FOR JOHN BECHTEL, SAID THAT HE CONSIDERED THAT THE CENTER CORNER OF SECTION 1-21-12 WAS **LOST**. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER CORNER OF SECTION 1-21-12 BY THE RETRACEMENT AND PRORATION OF A PERMANENT SURVEY BY ROBERT MILLIKEN IN 1875. [SEE SURVEY BOOK "C" ON PAGE 114]. HE NOTED IN HIS *REPORT OF SURVEY* THAT MILLIKEN HAD SET A POST FOR THE PERMANENT CENTER CORNER ON LINE BETWEEN THE SOUTH 1/4 CORNER AND THE NORTH 1/4 CORNER AND AT 40 CHAINS, HIS MEASURE, NORTH OF THE SOUTH 1/4 CORNER. HE RESET THE CENTER CORNER AS PER MILLIKEN'S SURVEY AND AT THE PRORATION OF MILLIKEN'S CHAIN FOR THIS LINE.
- 1) 22.4' SE TO A 40 D SPIKE & WASHER IN A 22" HACKBERRY TREE
 - 2) 23.95' ESE TO A 40 D SPIKE & WASHER IN THE SOUTH SIDE OF A HEDGE TREE
 - 3) 4.5' SOUTH TO A HEDGE TO THE EAST
 - 4) 16.5' EAST TO A HEDGE TO THE SOUTH
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
- 1) 2,998.31' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTH 1/4 CORNER OF SECTION 1-21-12 ON THE 4TH STANDARD PARALLEL [MILLIKEN = 3,006']
 - 2) 2,633.25' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 1-21-12 [MILLIKEN = 2,640']
 - 3) 2,663.31' EAST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE SE1/4 OF SECTION 1-21-12 ON THE RANGE LINE

CENTER CORNER 01-21-12