

NORTHWEST CORNER SECTION 02, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 576 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT THEY INTERSECTED THE NORTH BOUNDARY OF THE TOWNSHIP [4TH STANDARD PARALLEL SOUTH] AT 27.58 CHAINS WEST OF THE CORNER TO SECTIONS 34 & 35 AND 12.42 CHAINS EAST OF THE 1/4 CORNER ON THE SOUTH LINE OF SECTION 34 IN TOWNSHIP 20 SOUTH, RANGE 12 EAST. THEY SAID THAT **THEY SET A LIMESTONE 24" X 14" X 3"** FOR THE CORNER TO SECTIONS 2 & 3-21-12 ON THE 4TH STANDARD PARALLEL ON NOVEMBER 20, 1856.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 45.03 CHAINS SOUTH TO THE 21" X 9" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 2 & 3-21-12
 - 2) 85.03 CHAINS SOUTH TO THE 21" X 18" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 2, 3, 10 & 11-21-12
- 2) SAMUEL P. DAVIES, DEPUTY COUNTY SURVEYOR, IN SURVEY NUMBER 58, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 56 DATED JUNE 28, 1870 TO ESTABLISH THE 1/4 CORNER ON THE NORTH SIDE OF SECTION 3-21-12, ESTABLISH THE CENTER CORNER, AND DIVIDE THE NORTHWEST 1/4 BY A LINE RUNNING NORTH & SOUTH, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 3-21-12 ON THE 4TH STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 3-21-12
 - 2) 81.72 CHAINS WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 3-21-12
- 3) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A" ON PAGES 216 & 217 [PACKET 264 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] PETITIONED BY J. L. WILLIAMS AND OTHERS FOR A ROAD IN TOWNSHIP 20-12 THAT HE SURVEYED ON AUGUST 25, 1874, AND WAS ESTABLISHED AS A 40 FOOT WIDE ROAD ON OCTOBER 16, 1874 AS ATTESTED BY J. S. CRAIG, COUNTY CLERK, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF SECTION 2-21-12 ON THE 4TH STANDARD PARALLEL ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD INTERSECTS THE 4TH STANDARD PARALLEL AT **8 RODS WEST** OF THE SOUTHWEST CORNER OF SECTION 35-20-12, AND CONTINUES WEST ON THE 4TH STANDARD PARALLEL TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 33-20-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 2) THIS ROAD INTERSECTS THE SECTION LINE AT 144.13 RODS SOUTH OF THE WEST 1/4 CORNER OF SECTION 35-20-12; THEN CONTINUES NORTH ON THE SECTION LINES FOR 144.13 RODS TO THE WEST 1/4 CORNER OF SECTION 35-20-12 TO BEGIN THIS ROAD SURVEY

NORTHWEST CORNER 02-21-12