

**WEST 1/4 CORNER SECTION 04, TOWNSHIP 21 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 584 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 9" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-21-12.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 45.40 CHAINS NORTH TO THE 32" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-21-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL
  - 2) 40.00 CHAINS SOUTH TO THE 28" X 17" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-21-12
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 50 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 198 DATED MAY 16 & JUNE 6, 1872 TO ESTABLISH THE 1/4 CORNER ON THE NORTH SIDE OF SECTION 4-21-12 AND SUBDIVIDE THE NORTH 1/2 OF SAID SECTION 4, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 4-21-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 1,320' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 4-21-12
  - 2) 2,990' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 4-21-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL
  
- 3) STEVEN S. BROSEMER, L.S. 752, COUNTY SURVEYOR, IN SURVEY F04001 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR A SURVEY FOR THE LYON COUNTY HIGHWAY DEPARTMENT DATED APRIL 27, 1983, SAID THAT HE EXCAVATED WITH A COUNTY MAINTAINER FOR THE STONE AT THE WEST 1/4 CORNER OF SECTION - 21-12, BUT HE DID **NOT** FIND THE STONE. **HE CALCULATED COORDINATES** FOR THE POSITION OF THE WEST 1/4 CORNER OF SECTION 4-21-12, BUT HE DID **NOT MONUMENT** THE POSITION FOR THE WEST 1/4 CORNER OF SECTION 4-21-12 ON THIS SURVEY.

WEST QUARTER CORNER 04-21-12