

WEST 1/4 CORNER SECTION 05, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 591 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 5"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 6-21-12.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 44.61 CHAINS NORTH TO THE 24" X 11" X T" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5 & 6-21-12 ON THE 4TH STANDARD PARALLEL
 - 2) 40.00 CHAINS SOUTH TO THE 16" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-21-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 73 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 130 DATED JUNE 14, 1875 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 INTO NORTH & SOUTH HALVES IN SECTION 5-21-12, SAID THAT **HE FOUND THE STONE** AT THE WEST 1/4 CORNER OF SECTION 5-21-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320' NORTH TO THE STONE HE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE NW1/4 OF SECTION 5-21-12
 - 2) 2,937' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 5-21-12 ON THE 4TH STANDARD PARALLEL
 - 3) 1,323-1/2' SOUTH TO THE 15" X 4" X 5" STONE SET FOR THE PERMANENT WEST 1/2/4 CORNER OF THE SW1/4 OF SECTION 5-21-12
 - 4) 2,647' SOUTH TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF SECTION 5-21-12

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 123, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 123 DATED SEPTEMBER 21-28, 1885 ORDERED BY SAMUEL BURDETTE TO SURVEY SECTION 6-21-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 6-21-12 ON THIS **PERMANENT SURVEY**. HE NOTED THAT "THE GOVERNMENT SURVEY WAS SHORT 16 FEET TO THE MILE" ALONG THE RANGE LINE.
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 2,640' SOUTH TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 6-21-12
 - 2) 1,320' WEST TO THE STAKE HE SET FOR THE SOUTH 1/4/4 CORNER OF THE NE1/4 OF SECTION 6-21-12
 - 3) 2,640' WEST TO THE 3" X 8" X 12" SANDSTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 6-21-12
 - 4) 3,960' WEST TO THE STAKE HE SET FOR THE SOUTH 1/4/4 CORNER OF THE NW1/4 OF SECTION 6-21-12

WEST QUARTER CORNER 05-21-12