

NORTH 1/4 CORNER SECTION 08, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 590 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 5 & 8-21-12.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 39.79 CHAINS WEST TO THE 16" X 11" X 6" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 5, 6, 7 & 8-21-12
- 2) 39.79 CHAINS EAST TO THE 28" X 17" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-21-12

- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 73 OF THE 8TH TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 130 DATED JUNE 14, 1875 TO ESTABLISH THE CENTER CORNER AND SUBDIVIDE THE NORTHWEST 1/4 AND THE SOUTHWEST 1/4 INTO NORTH & SOUTH HALVES, ALL IN SECTION 5-21-12, SAID THAT **HE FOUND THE STONE AT THE SOUTH 1/4 CORNER OF SECTION 5-17-12 ON THIS PERMANENT SURVEY.**

HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 1,320' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NW1/4 OF SECTION 5-21-12
- 2) 2,640' NORTH TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 5-21-12
- 3) 3,960' NORTH TO THE STONE HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NW1/4 OF SECTION 5
- 4) 5,606' NORTH TO THE POST HE SET FOR THE PERMANENT NORTH 1/4 CORNER OF SECTION 5-21-12 ON THE 4TH STANDARD PARALLEL

- 3) IN A FIELD BOOK MARKED "NUMBER 39 PRELIMINARY NOTES FAS ROUTE NUMBER 1122" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE 1 IT **SHOWS A 1/2" REBAR** AT P. O. T. STATION 126+27.2 AT THE NORTH 1/4 CORNER OF SECTION 8-21-12.

- 1) 23.9' SSW TO A SPIKE IN A BLAZED MAPLE TREE
- 2) 25.3' NNE TO A BENT SPIKE IN A FENCE POST
- 3) IN LINE WITH A FENCE TO THE NORTH
- 4) 2,627.2' WEST TO NORTHWEST CORNER OF SECTION 8
- 5) 2,628.6' EAST TO NORTHEAST CORNER OF SECTION 8

- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED FEBRUARY 23, 2005, FOR PROJECT NUMBER 05054-02, SURVEY F08001 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR THE SURVEY OF A 10.0 ACRE TRACT IN THE EAST HALF OF THE SOUTHWEST QUARTER OF SECTION 8, SAID THAT **HE FOUND A 1/2" REBAR WITH HIS RED "LS 752" CAP** AT THE NORTH 1/4 CORNER OF SECTION 8-21-12 FROM EXISTING REFERENCE TIES AT THE COUNTY ENGINEER'S OFFICE.

- 1) 43.5' NW TO THE SE CORNER OF A TELEPHONE PEDESTAL AT THE GROUND
- 2) 31.0' SE TO A 40 D NAIL & WASHER IN A POWER POLE
- 3) 28.8' SOUTH TO A 40 D NAIL & WASHER IN A BRACE POST
- 4) IN LINE WITH A FENCE TO THE NORTH
- 5) 9.5' WEST TO A FENCE TO THE SOUTH-EXTENDED
- 6) 2.0' NORTH TO THE CENTERLINE TRAVELED WAY OF COUNTY ROAD 60 EAST-WEST

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

- 1) 4,620.72' SOUTH TO THE 1/2" REBAR WITH HIS RED "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE 10.0 ACRE TRACT

HIS INFORMATION IS CONTINUED ON PAGE 2

- 2) 5,280.72' SOUTH TO THE 1/2" REBAR WITH HIS RED "LS 752" CAP HE FOUND AT THE SOUTHEAST CORNER OF THE SW1/4 OF SECTION 8-21-12, AND THE SOUTHEAST CORNER OF THE 10.0 ACRE TRACT

NORTH QUARTER CORNER 08-21-12