

NORTHWEST CORNER SECTION 09, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 584 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 28" X 17" X 4"** FOR THE CORNER TO SECTIONS 4, 5, 8 & 9-21-12.

THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:

- 1) 40.00 CHAINS NORTH TO THE 18" X 9" X 5" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 5-21-12
 - 2) 85.40 CHAINS NORTH TO THE 32" X 14" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 4 & 5-21-12 ON THE 4TH STANDARD PARALLEL
 - 3) 39.94 CHAINS EAST TO THE 18" X 13" X 4" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 4 & 9-21-12
 - 4) 79.88 CHAINS EAST TO THE 21" X 12" X 5" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 3, 4, 9 & 10-21-12
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 6 TO 8 FOR ROAD NUMBER 2 BY A PETITION BY JOSEPH SPANDEN AND OTHERS [PACKET 110 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON AUGUST 28, 1878, WAS ESTABLISHED ON JULY 7, 18718 AS A 60 FOOT WIDE ROAD, AND WAS RECORDED ON NOVEMBER 26, 1878 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-21-12 TO COMMENCE THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 5,280 FEET TO THE NORTHWEST CORNER OF SECTION 8-21-12; THEN CONTINUED WEST ON THE SECTION LINE FOR 5,280 FEET TO THE NORTHWEST CORNER OF SECTION 7-21-12 ON THE RANGE LINE; THEN EXTENDS NORTH ON THE RANGE LINE FOR 5,280 FEET TO THE NORTHWEST CORNER OF SECTION 6-21-12 AT THE TOWNSHIP CORNER ON THE 4TH STANDARD PARALLEL AT THE TERMINUS OF THIS ROAD SURVEY
- 3) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE LEFT PAGE 159 DATED SEPTEMBER 4, 1878, APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-21-12 TO BEGIN THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR TWO MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 7-21-12 ON THE RANGE LINE
- 4) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 34 RECORDED IN ROAD RECORD BOOK "A-1" ON PAGES 134 TO 138 PETITION BY H. M. WILSON AND OTHERS FOR A COUNTY ROAD IN TOWNSHIPS 20-12 AND 21-12 [PACKET 119 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON JUNE 20, 1879, WAS ESTABLISHED AS A 50 FOOT WIDE ROAD ON JULY 7, 1879, AND WAS RECORDED ON JULY 16, 1879 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE SOUTHEAST OF SECTION 5-21-12 ON THIS ROAD SURVEY.

HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:

- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 5,280' TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-21-12 ON THE 4TH STANDARD PARALLEL; THEN EXTENDS WEST ON THE 4TH STANDARD PARALLEL FOR 761' TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12; THEN EXTENDS NORTH ON THE 1/2 SECTION

LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12 TO COMMENCE THIS ROAD SURVEY

- 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-21-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 5) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE BOTTOM RIGHT SIDE PAGE 168 BUT NOT DATED, FOR A COUNTY ROAD IN TOWNSHIPS 20-12 AND 21-12, APPARENTLY **FOUND THE STONE** AT THE SOUTHEAST CORNER OF SECTION 5-21-12 ON THIS ROAD SURVEY. [**NOTE:** HIS DRAWING DOES **NOT** MATCH HIS DESCRIPTION IN HIS SURVEY NOTES – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR]
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THIS ROAD EXTENDS NORTH ON THE SECTION LINES FOR 5,280' TO THE STONE HE FOUND AT THE NORTHEAST CORNER OF SECTION 5-21-12 ON THE 4TH STANDARD PARALLEL; THEN EXTENDS WEST ON THE 4TH STANDARD PARALLEL FOR 761' TO THE STONE HE FOUND AT THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12; THEN EXTENDS NORTH ON THE 1/2 SECTION LINE TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE SE1/4 OF SECTION 32-20-12 TO COMMENCE THIS ROAD SURVEY
 - 2) THIS ROAD EXTENDS EAST ON THE SECTION LINES TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 2-21-12 AT THE TERMINUS OF THIS ROAD SURVEY
- 6) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON RIGHT SIDE PAGE 200 DATED DECEMBER 8, 1880, FOR TWO ROAD SURVEYS IN TOWNSHIP 21-12 APPARENTLY **FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-21-12 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING DISTANCE:
- 1) THE FIRST ROAD EXTENDS EAST ON THE SECTION LINE FOR 698 FEET; THEN SOUTH FOR 1,320 FEET; THEN WEST FOR 698 FEET TO THE SECTION LINE; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 4-3/4 MILES TO THE SOUTHWEST CORNER OF SECTION 33-21-12 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY
- 7) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY FOR ROAD NUMBER 104 RECORDED IN ROAD RECORD BOOK "B" ON PAGES 2 TO 4 FOR PETITIONED BY B. WIELAND AND OTHERS FOR TWO COUNTY ROADS IN TOWNSHIP 21-12 [PACKET 346 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON DECEMBER 8, 1880, WERE ESTABLISHED AT 50 FOOT WIDE FOR THE NORTH AND SOUTH ROAD AND 40 FOOT WIDE FOR THE EAST AND WEST ROAD ON JANUARY 10, 1881 AS NOTED BY J. M. GRIFFITH, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, AND RECORDED ON MAY 4, 1881 BY WILLIAM F. EWING, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 8-21-12 TO COMMENCE THE FIRST ROAD ON THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
- 1) THE FIRST ROAD EXTENDS EAST ON THE SECTION LINE FOR 698 FEET; THEN SOUTH FOR 1,320 FEET; THEN WEST FOR 698 FEET TO THE SECTION LINE; THEN CONTINUES SOUTH ON THE SECTION LINES FOR 4-3/4 MILES TO THE SOUTHWEST CORNER OF SECTION 33-21-12 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE AT THE TERMINUS OF THE FIRST ROAD ON THIS ROAD SURVEY

CONTINUED ON PGE 3

- 8) IN A FIELD BOOK MARKED "NUMBER 39 PRELIMINARY NOTES FAS ROUTE NUMBER 1122" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE ON PAGE NUMBER 1 IT SHOWS A **5/8" REBAR AT P. I. STATION 158+55.8** AT THE NORTHWEST CORNER OF SECTION 9. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS REBAR MAY HAVE BEEN "HEELED-IN" FOR THE PROJECT!! WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
- 1) 26.7' SE TO A NAIL & WASHER IN A BLAZED ELM SPROUT
 - 2) 27' SW TO A NAIL & WASHER IN A BLAZED ELM SPROUT
- 9) STEVEN S. BROSEMER, L.S. 752, COUNTY SURVEYOR, IN SURVEY F04001 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR A SURVEY FOR THE LYON COUNTY HIGHWAY DEPARTMENT DATED APRIL 27, 1983, SAID THAT HE **"DID NOT DIG"** FOR THE STONE AT THE SOUTHWEST CORNER OF SECTION 4-21-12.

NORTHWEST CORNER 09-21-12