

CENTER 1/4 CORNER SECTION 10, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 206 DATED MAY 2, 1878 ORDERED BY H. BREINER TO SURVEY THE NORTHEAST 1/4 OF SECTION 10-21-12 AND THE NORTHWEST 1/4 OF SECTION 11-21-12, SAID THAT **HE SET A STONE** FOR THE PERMANENT CENTER CORNER OF SECTION 10-21-12 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS **PERMANENT SURVEY**.

HIS SURVEY NOTES/ DRAWING SHOW THE FOLLOWING INFORMATION:

- 1) 159 RODS, 24 LINKS NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 10-21-12
 - 2) 160 RODS, 10.3 LINKS EAST TO THE STONE HE FOUND AT THE EAST 1/4 CORNER OF SECTION 10-21-12
- 2) STEVEN S. BROSEMER, L.S. 752, IN A SECTION CORNER REPORT DATED JUNE 7, 2007 BUT NOT TURNED IN TO THE COUNTY SURVEYOR UNTIL APRIL 14, 2012 FOR PROJECT 07124-02, SURVEY F10002 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR A SURVEY OF THE NORTH HALF OF THE NORTHWEST QUARTER OF SECTION 10-21-12 FOR JOHN GILLIGAN, SAID THAT HE CONSIDERED THAT THE CENTER CORNER OF SECTION 10-21-12 WAS **OBLITERATED**. HE RESET THIS CORNER BY THE PHYSICAL EVIDENCE OF A PRIOR PERMANENT SURVEY BY J. H. HIBBEN PERFORMED ON MAY 2, 1878. HE NOTED ON HIS SURVEY THAT THE HIBBEN SURVEY ESTABLISHED THE CENTER CORNER OF SECTION 10-21-12 AT THE INTERSECTION OF THE LINES BETWEEN THE OPPOSITE QUARTER CORNERS. HE RESET THE CENTER CORNER BY THE PHYSICAL EVIDENCE THAT FOUND TO BE IN HARMONY WITH THAT PERMANENT SURVEY RECORDED IN BOOK "C" ON PAGE 206 IN THE LYON COUNTY ENGINEER'S OFFICE. **HE SET A 5/8" X 24" REBAR WITH HIS "LS 752" CAP** FOR THE CENTER OF SECTION 10-21-12.
- 1) ON THE WEST SIDE OF A CORNER FENCE POST
 - 2) IN LINE WITH A FENCE TO THE NORTH, SOUTH AND EAST
 - 3) 17.30' SOUTH TO A CONCRETE NAIL & WASHER IN THE SOUTH GATE POST
 - 4) 10.55' NORTH TO A CONCRETE NAIL & WASHER IN THE TOP OF THE NORTH BRACE POST
- HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:**
- 1) 2,656.97' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 10-21-12
 - 2) 1,324.70' NORTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 10-21-12
 - 3) 2,643.39' NORTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF SECTION 10-21-12
 - 4) 2,648.50' EAST TO THE SQUARE #4 REBAR HE FOUND AT THE SOUTHEAST CORNER OF THE NE1/4 OF SECTION 10-21-12

CENTER CORNER 10-21-12