

WEST 1/4 CORNER SECTION 11, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 575 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 33" X 12" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 10 & 11-21-12.
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, BY FRANK P. MACLEMAN, DEPUTY COUNTY SURVEYOR, IN A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "C" ON PAGE 206 DATED MAY 2, 1878 ORDERED BY H. BREINER TO SURVEY THE NORTHEAST 1/4 OF SECTION 10-21-12 AND THE NORTHWEST 1/4 OF SECTION 11-21-12, SAID THAT **HE FOUND THE STONE** AT THE EAST 1/4 CORNER OF SECTION 10-21-12 ON THIS **PERMANENT SURVEY**.
HIS SURVEY NOTES/ DRAWING SHOW THE FOLLOWING INFORMATION
 - 1) 160 RODS, 10.3 LINKS WEST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 10-21-12
 - 2) 158 RODS, 12-1/2 LINKS EAST TO THE STONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 11-21-10
- 3) IN A FIELD BOOK MARKED "NUMBER 36 MARCH 1946 MISCELLANEOUS NOTES" IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE, ON PAGE 21 FOR G. W. GASCHE, ON MAY 29, 1946, IT SHOWS AN **IRON PIN** AT THE WEST 1/4 CORNER OF SECTION 11-21-12. **VERIFY AND CHECK FOR THE STONE OF RECORD BEFORE USING AS THIS IRON PIN MAY HAVE BEEN "HEELED-IN" FOR THIS PROJECT – WARREN CHIP WOODS, L.S. 603, COUNTY SURVEYOR**
 - 1) 22' WEST TO A CORNER FENCE POST
 - 2) IN LINE WITH A FENCE TO THE WEST
- 4) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JUNE 7, 2007 BUT NOT TURNED IN TO THE COUNTY SURVEYOR UNTIL APRIL 14, 2012 FOR PROJECT 07124-02, SURVEY F10002 IN THE SURVEY FILE FOR TOWNSHIP 21-12 FOR A SURVEY OF THE NORTH HALF OF THE NORTHWEST QUARTER OF SECTION 10-21-12 FOR JOHN GILLIGAN, SAID THAT **HE FOUND A 1/2" SQUARE REBAR** AT THE EAST 1/4 CORNER OF SECTION 10-21-10 FROM EXISTING REFERENCE TIES ON FILE IN THE COUNTY ENGINEER'S OFFICE.
 - 1) IN LINE WITH FENCES TO THE EAST AND WEST EXTENDED
 - 2) 1.0' EAST TO THE CENTERLINE OF TRAVELED WAY FOR COUNTY ROAD "T"
 - 3) 45.65' NW TO A CONCRETE NAIL & WASHER IN THE NORTH GATE POST
 - 4) 29.80' WEST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POST
 - 5) 25.70' EAST TO A CONCRETE NAIL & WASHER IN A CORNER FENCE POSTHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION
 - 1) 2,642.84' NORTH TO THE SQUARE #4 REBAR HE FOUND AT THE NORTHEAST CORNER OF THE NE1/4 OF SECTION 10-21-12
 - 2) 2,648.50' WEST TO THE 5/8" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHEAST CORNER OF THE NW1/4 OF SECTION 10-21-12
 - 3) 5,305.47' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 10-21-12

WEST QUARTER CORNER 11-21-12