

**NORTH 1/4 CORNER SECTION 13, TOWNSHIP 21 SOUTH, RANGE 12 EAST**

- 1) ON PAGE 570 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 3"** FOR THE 1/4 CORNER BETWEEN SECTIONS 12 & 13-21-12.  
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
  - 1) 40.35-1/2 CHAINS WEST TO THE 22" X 10" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 11, 12, 13 & 14-21-12
  - 2) 40.35-1/2 CHAINS EAST TO THE 24" X 12" X 2" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 12 & 13-11-12 ON THE EAST TOWNSHIP BOUNDARY
  
- 2) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 67 OF THE 7<sup>TH</sup> TERM, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "B" ON PAGE 215 DATED OCTOBER 2, 1872 TO FIND THE CORNERS OF THE NORTH 1/2 OF THE NORTHWEST 1/4 OF SECTION 12-21-12, STATES THAT **HE FOUND THE STONE** AT THE SOUTH 1/4 CORNER OF SECTION 12-21-12 ON THIS **PERMANENT SURVEY**.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,646' NORTH TO THE WALNUT POST HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 12-21-12
  - 2) 3,969' NORTH TO THE WALNUT POST HE SET FOR THE PERMANENT EAST 1/2/4 CORNER OF THE NW1/4 OF SECTION 12-21-12
  - 3) 5,292' NORTH TO THE STONE HE FOUND AT THE NORTH 1/4 CORNER OF SECTION 12-21-12
  
- 3) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 35, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 216 DATED NOVEMBER 18, 1901 ORDERED BY G. W. GASCHÉ TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 12-21-12, SAID THAT **HE FOUND THE 1/4 STONE IN LINE WITH A HEDGE AND A FENCE** AT THE SOUTH 1/4 CORNER OF SECTION 12-21-12 ON THIS **PERMANENT SURVEY**. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 51" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.  
HIS SURVEY NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 2,674' WEST TO THE STAKE HE SET FOR THE TEMPORARY SOUTHWEST CORNER OF SECTION 12-21-12
  - 2) 2,674' EAST TO THE BROKEN GOVERNMENT STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 12-21-12 ON THE RANGE LINE
  - 3) 2,651' NORTH TO THE 4" X 4" X 18" SANDSTONE HE SET FOR THE PERMANENT CENTER CORNER OF SECTION 12-21-12
  - 4) 3,976-1/2' NORTH TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE S1/2 OF THE NE1/4 OF SECTION 12-21-12
  - 5) 5,302' NORTH TO THE FLAG HE SET FOR THE NORTH 1/4 CORNER OF SECTION 12-21-12
  
- 4) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 121, A ROAD SURVEY RECORDED IN SURVEY BOOK "F" ON PAGE 202 DATED APRIL 11, 1905 FOR A ROAD IN SECTION 13-21-12 FOR J. L. STRATTON, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE IN LINE WITH A HEDGE AND A FENCE** AT THE NORTH 1/4 CORNER OF SECTION 13-21-12 ON THIS ROAD SURVEY FOR A 50 FOOT WIDE ROAD.  
HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:  
HIS INFORMATION IS CONTINUED ON PAGE 2

- 1) HE RAN 60 FEET EAST ON THE SECTION LINE AND HE SET A LIMESTONE 18" X 6" X 4" TO END THIS ROAD SURVEY, THENCE S. 27°15' W. FOR 130 FEET TO THE 12" X 4" X 3" SANDSTONE HE SET AT 115.5' SOUTH OF THE NORTH 1/4 CORNER OF SECTION 13, THENCE WEST PARALLEL TO AND 115.5' DISTANCE FROM THE SECTION LINE FOR 2,647 FEET TO THE 12" X 6" X 2" SANDSTONE HE SET ON THE SECTION LINE AT 115.5 FEET SOUTH OF THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 13-21-12 TO BEGIN THIS ROAD SURVEY
  - 2) THE OLD ROAD ON THE SECTION LINE BETWEEN THE BEGINNING AND ENDING OF THIS ROAD SURVEY WAS VACATED
- 5) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN A ROAD SURVEY FOR ROAD NUMBER 600 RECORDED IN ROAD RECORD BOOK "D" ON PAGES 269 THROUGH 272 PETITIONED BY J. L. STRATTON AND OTHERS FOR RELOCATING A ROAD IN SECTION 13-21-12 [PACKET 745 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE] THAT HE SURVEYED ON APRIL 11, 1905, WAS GRANTED AS A 50 FOOT WIDE ROAD, BEING 25 FEET EACH SIDE OF THE LINE AS SURVEYED, ON MAY 4, 1905 AS NOTED BY W. H. MAPES, CHAIRMAN OF THE BOARD OF COUNTY COMMISSIONERS, ATTESTED BY W. F. EGGERS, COUNTY CLERK, AND RECORDED ON MAY 29, 2905 BY ALVA J. SMITH, COUNTY SURVEYOR, SAID THAT **HE FOUND THE STONE AT THE NORTH 1/4 CORNER OF SECTION 13-21-12 [ IN LINE WITH A HEDGE AND FENCE]** ON THIS ROAD SURVEY. HIS SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
- 1) HE RAN 60 FEET EAST ON THE SECTION LINE AND HE SET A LIMESTONE 18" X 6" X 4" TO END THIS ROAD SURVEY, THENCE S. 27°15' W. FOR 130 FEET TO THE 12" X 4" X 3" SANDSTONE HE SET AT 115.5' SOUTH OF THE NORTH 1/4 CORNER OF SECTION 13, THENCE WEST PARALLEL TO AND 115.5' DISTANCE FROM THE SECTION LINE FOR 2,647 FEET TO THE 12" X 6" X 2" SANDSTONE HE SET ON THE SECTION LINE AT 115.5 FEET SOUTH OF THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 13-21-12 TO BEGIN THIS ROAD SURVEY
  - 2) THE OLD ROAD ON THE SECTION LINE BETWEEN THE BEGINNING AND ENDING OF THIS ROAD SURVEY WAS VACATED

NORTH QUARTER CORNER 13-21-12