

WEST 1/4 CORNER SECTION 13, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 570 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 20" X 10" X 4"** FOR THE 1/4 CORNER BETWEEN SECTIONS 13 & 14-21-12.

- 2) ALVA J. SMITH, COUNTY SURVEYOR FROM 1900 THROUGH 1906, IN SURVEY NUMBER 35, A **PERMANENT SURVEY** RECORDED IN SURVEY BOOK "E" ON PAGE 216 DATED NOVEMBER 18, 1901 ORDERED BY G. W. GASCHÉ TO LOCATE AND PERMANENTLY ESTABLISH THE CORNERS AND BOUNDARIES OF THE SOUTH 1/2 OF THE NORTHEAST 1/4 OF SECTION 12-21-12, SAID THAT **HE FOUND THE STONE LOOSE IN THE GROUND** AT THE WEST 1/4 CORNER OF SECTION 13-21-12 ON THIS **LEGAL SURVEY**. HE DID NOT SAY IF HE RESET THE STONE TO ITS PROPER LOCATION. HIS FIELD NOTES ARE IN HIS BOOK 3 ON PAGE 14 IN THE "KRETSINGER COLLECTION" OF FIELD BOOKS, AND THERE IS ADDITIONAL INFORMATION IN PACKET "M 51" IN MISCELLANEOUS DRAWER NUMBER 2 IN THE VAULT IN THE COUNTY ENGINEER'S OFFICE.

WEST QUARTER CORNER 13-21-12