

NORTHWEST CORNER SECTION 30, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 104 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 16" X 13" X 4"** FOR THE CORNER TO SECTIONS 19 & 30-21-12 ON THE WEST TOWNSHIP BOUNDARY ON NOVEMBER 14, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 15" X 12" X 3" LIMESTONE THEY SET FOR THE WEST 1/4 CORNER OF SECTION 30-21-12
 - 2) 80.00 CHAINS SOUTH ON THE WEST TOWNSHIP BOUNDARY TO THE 16" X 12" X 3" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 30 & 31-21-12
 - 3) 29.87 CHAINS EAST TO THE 19" X 13" X 3" LIMESTONE THEY SET FOR THE 1/4 CORNER BETWEEN SECTIONS 19 & 30-21-12
 - 4) 69.87 CHAINS EAST TO THE 20" X 15" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 19, 20, 29 & 30-21-12

- 2) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN SURVEY NUMBER 51, A ROAD SURVEY FOR A ROAD IN TOWNSHIP 21, RANGE 11 RECORDED IN SURVEY BOOK "E" ON PAGE 51 DATED AUGUST 12 & 13, 1884 FOR DARIUS BUCK, PRINCIPAL PETITIONER, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 25-21-11 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-21-11; THEN EXTENDS WEST ON THE SECTION LINES WITH ANGLE STONES IN THE NE1/4 OF SECTION 27-21-11 AND ANGLE STONES IN THE NW1/4 OF SECTION 28-21-11 TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-2-11 TO BEGIN THIS ROAD SURVEY. SEE THE SURVEY FOR THE LOCATION OF THE ANGLE STONES

- 3) R. H. EDMISTON, COUNTY SURVEYOR FROM 1884 TO 1887, IN A ROAD SURVEY FOR ROAD NUMBER 287 RECORDED IN ROAD RECORD BOOK "C" ON PAGES 98 TO 100 PETITIONED BY DARIUS BUCK AND OTHERS FOR A COUNTY ROAD IN TOWNSHIP 21-10 [PACKET 549 IN THE VAULT IN THE COUNTY SURVEYOR'S OFFICE], THAT HE SURVEYED ON AUGUST 13, 1884 THAT THE VIEWERS RECOMMENDED TO BE 50 FEET WIDE, BUT WAS ORDERED BY THE COUNTY COMMISSIONERS TO BE A 40 FOOT WIDE ROAD ON JANUARY 8, 1885 AS NOTED BY P. Y. HALLBERG, CHAIRMAN, AND WAS RECORDED ON MARCH 24, 1885 BY ROLAND LAKIN, COUNTY CLERK, SAID THAT **HE FOUND THE STONE** AT THE NORTHEAST CORNER OF SECTION 25-21-11 ON THE RANGE LINE AT THE TERMINUS OF THIS ROAD SURVEY.
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
 - 1) THIS ROAD EXTENDS WEST ON THE SECTION LINES FOR 2 MILES TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 26-21-11; THEN EXTENDS WEST ON THE SECTION LINES WITH ANGLE STONES IN THE NE1/4 OF SECTION 27-21-11 AND ANGLE STONES IN THE NW1/4 OF SECTION 28-21-11 TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF SECTION 29-2-11 TO BEGIN THIS ROAD SURVEY. SEE THE SURVEY FOR THE LOCATION OF THE ANGLE STONES

- 4) STATE HIGHWAY COMMISSION SURVEYORS J. L. DOLE AND C. A. MARLATTE IN 1930 HAD TO REWORK THE SURVEY BY OAKES, DOLE & BISHOP, AND THEY SAID THAT **THEY FOUND A LARGE SANDSTONE "WELL SET"** WITH SMALLER STONES ON TOP AT THE NORTHEAST CORNER OF SECTION 25-21-11 ON THE RANGE LINE. A COPY OF THEIR FIELD NOTES ARE IN THE SURVEY FILE FOR TOWNSHIP 20-11 ON PAGE 15 A COPY OF THEIR FIELD NOTES IS IN THE SURVEY FILE FOR TOWNSHIP 20-11 ON PAGE 11 OF THE NOTES MARKED "KDOT 2".

- 1) 22.4' NE TO A SPIKE IN A CORNER FENCE POST
 - 2) 31.5' SE TO A SPIKE IN A CORNER FENCE POST
 - 3) 24.8' NW TO THE EAST CORNER OF THE NORTHEAST WINGWALL OF A CULVERT
 - 4) 28.2' SW TO THE EAST CORNER OF THE SOUTHEAST WINGWALL OF A CULVERT
- 5) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-11 SHOWS A **SANDSTONE** AT THE "SE CORNER SECTION 24-21-11" ON THE RANGE LINE.
- 1) 22.4' NE TO A SPIKE IN A CORNER FENCE POST
 - 2) 31.5' SE TO A SPIKE IN A CORNER FENCE POST
 - 3) 24.8' SW TO THE EAST CORNER OF THE NORTHEAST WINGWALL
 - 4) 28.2' SW TO THE EAST CORNER OF THE SOUTHEAST WINGWALL
- 6) KRETSINGER REFERENCE TIE BOOK 13 ON A FOLDED OUT SHEET STAPLED TO THE LAST PAGE OF THE BOOK AND LABELED "SECTION CORNERS IN TOWNSHIP 21 S, R 11 E" SHOWS A **SANDSTONE** AT THE "NE CORNER SECTION 25-21-11" ON THE RANGE LINE.
- 1) 22.4' NE TO A SPIKE IN A CORNER FENCE POST
 - 2) 31.5' SE TO A SPIKE IN A CORNER FENCE POST
 - 3) 24.8' NW TO THE EAST CORNER OF THE NORTHEAST WINGWALL
 - 4) 28.2' SW TO THE EAST CORNER OF THE SOUTHEAST WINGWALL
- 7) THE KRETSINGER REFERENCE TIE BOOK FOR TOWNSHIP 21-11 SHOWS A **5/8" REBAR** AT THE "SE CORNER SECTION 24-21-11" ON THE RANGE LINE ON MARCH 24, 1974. THE NOTE SAID "THIS PIN WAS SET WHERE WE FOUND A NEST OF STONES, PART BEING SANDSTONE".
- 1) 30.5' NE TO A CORNER FENCE POST
 - 2) 30.5' SE TO A CORNER FENCE POST
- 8) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED NOVEMBER 14, 1983, SAID THAT HE EXCAVATED THE INTERSECTION AT THE NORTHEAST CORNER OF SECTION 25-21-11 ON THE RANGE LINE WITH A COUNTY MAINTAINER, AND THE STONE CITED IN THE KRETSINGER BROWN TIE BOOKS WAS **NOT** FOUND. **HE DID FIND A 5/8" REBAR** THAT WAS SET BY LESLIE M. GOULD, L.S. 142, COUNTY SURVEYOR FROM 1953 TO 1978, ON MARCH 28, 1974 AT THE NORTHEAST CORNER OF SECTION 25-21-11 ON THE RANGE LINE. HE DID **NOT** INDICATE IF HE ACCEPTED THIS FOUND 5/8" REBAR AS THE NORTHEAST CORNER OF SECTION 25-21-11.
- 1) NO TIES WERE GIVEN ON THE REPORT

NORTHWEST CORNER 30-21-12