

SOUTH 1/4 CORNER SECTION 36, TOWNSHIP 21 SOUTH, RANGE 12 EAST

- 1) ON PAGE 101 OF THE GLO ORIGINAL FIELD NOTES IN THE DRAFTING ROOM IN THE COUNTY ENGINEER'S OFFICE IT STATES THAT **THEY SET A LIMESTONE 18" X 12" X 3"** FOR THE SOUTH 1/4 CORNER OF SECTION 36-21-12 ON THE TOWNSHIP LINE AND THE COUNTY LINE ON NOVEMBER 13, 1856.
THE GOVERNMENT SURVEY NOTES SHOW THE FOLLOWING INFORMATION:
 - 1) 40.00 CHAINS WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 18" X 12" X 4" LIMESTONE THEY SET FOR THE CORNER TO SECTIONS 35 & 36-21-12
 - 2) 40.00 CHAINS EAST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE 24" X 12" X 2" LIMESTONE THEY SET FOR THE CORNER TO TOWNSHIPS 21 & 22 SOUTH, RANGES 12 & 13 EAST AT THE SOUTHEAST CORNER OF SEC. 36-21-12

- 2) J. HARRISON PARKMAN, COUNTY SURVEYOR FROM 1907 TO 1915, IN A **PERMANENT SURVEY** RECORDED IN PERMANENT SURVEY BOOK 1 ON PAGE 20 AT THE REQUEST OF C. H. DAY FOR ANNA DAY, HIS WIFE, TO SURVEY THEIR TRACT IN SECTION 36-21-12, SAID THAT **HE DROVE A HEDGE STAKE AT SOUTH OF THE CENTER OF A HEDGE RUNNING NORTH** FOR THE SOUTH 1/4 CORNER OF SECTION 36-21-12 ON THE TOWNSHIP LINE AND THE LYON AND GREENWOOD COUNTY LINE ON THIS **PERMANENT SURVEY**. THE SURVEY WAS MADE ON JUNE 10 & 11, 1907 AND WAS ENTERED ON SEPTEMBER 14, 1907.
HIS NOTES/DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,320' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE HEDGE STAKE HE DROVE FOR THE SOUTH 1/8TH CORNER OF THE SW1/4 OF SECTION 36-21-12, AT 9 FEET WEST OF A LINE OF FENCE TO THE NORTH
 - 2) 2,640' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE HEDGE STAKE HE DROVE FOR THE SOUTHWEST CORNER OF SECTION 36-21-12
 - 3) 10,560' WEST ON THE TOWNSHIP LINE AND COUNTY LINE TO THE STONE HE FOUND AT THE SOUTH 1/4 CORNER OF SECTION 34-21-12
 - 4) 1,320' NORTH TO THE HEDGE STAKE HE DROVE FOR THE WEST 1/8TH CORNER OF THE SE1/4 OF SECTION 36-21-12, AT 9" NORTH OF A LINE OF FENCE RUNNING EAST AND 1 FOOT WEST OF A LINE OF FENCE RUNNING SOUTH

SOUTH QUARTER CORNER 36-21-12