

**CENTER 1/4 CORNER SECTION 03, TOWNSHIP 21 SOUTH, RANGE 13 EAST**

- 1) C. H. RICE, DEPUTY COUNTY SURVEYOR, IN A SURVEY RECORDED IN SURVEY BOOK "D" ON PAGE 128 DATED APRIL 26, 1882 TO SUBDIVIDE SECTION 3-21-13, SAID THAT **HE SET A STONE** FOR THE CENTER CORNER OF SECTION 3-21-13 AT THE INTERSECTION OF THE LINES FROM THE OPPOSITE 1/4 CORNERS ON THIS SURVEY.
  
- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED NOVEMBER 28, 2005, FOR PROJECT NUMBER 05392-02, SURVEY F03002 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A SURVEY OF THE SOUTH LINE OF THE NORTHWEST FRACTIONAL QUARTER OF SECTION 3-21-13 FOR ALMA JEAN MAUTZ, SAID THAT **HE FOUND A CORNER FENCE POST** IN A REASONABLE POSITION FOR THE CENTER CORNER OF SECTION 3-21-13 AS PER THE PERMANENT SURVEY BY C. H. RICE, DATED APRIL 1882 AND FILED IN PERMANENT SURVEY BOOK "D" ON PAGE 129. **HE SET A 5/8" X 24" REBAR WITH LYON COUNTY CAP ON THE SOUTH SIDE OF THE CORNER FENCE POST** FOR THE CENTER CORNER OF SECTION 3-21-13.
  - 1) 32.40' NNE TO A 40 D NAIL & SHINER IN A 30" COTTONWOOD TREE
  - 2) 7.75' EAST TO A 40 D NAIL & SHINER IN A 10" ELM TREE
  - 3) IN LINE WITH A FENCE TO THE NORTH
  - 4) 1,335.49' WEST TO A 1/2" X 24" REBAR SET
  - 5) NO OTHER REFERENCES AVAILABLE

HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:

  - 1) 1,335.49' WEST TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTHWEST CORNER OF THE E1/2 OF THE NW1/4 OF SECTION 3-21-13
  - 2) 2,670.99' WEST TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTHWEST CORNER OF THE NW1/4 OF SECTION 3-21-13

CENTER CORNER 03-21-13