

**NORTH 1/4 CORNER SECTION 06, TOWNSHIP 21 SOUTH, RANGE 13 EAST**

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 16, A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 16 DATED MARCH 1-5, 1870 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 6-21-13, SAID THAT **HE SET A STONE** FOR THE NORTH 1/4 CORNER OF SECTION 6-21-12 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON THIS **PERMANENT SURVEY**.
- 2) J. H. HIBBEN, COUNTY SURVEYOR FROM 1875 TO 1882, IN A ROAD SURVEY RECORDED IN SURVEY BOOK "C" ON THE RIGHT PAGE 146 DATED APRIL 8, 1876, APPARENTLY **FOUND THE STONE** AT THE NORTHWEST CORNER OF THE NORTHEAST 1/4 OF SECTION 6-21-13 ON THE 4<sup>TH</sup> STANDARD PARALLEL ON THIS ROAD SURVEY.  
HIS SURVEY NOTES SHOWS THE FOLLOWING INFORMATION:
  - 1) 228' WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE SOUTHWEST CORNER OF SECTION 31-20-13
  - 2) 5,695' SOUTH TO THE SOUTHWEST CORNER OF THE SE1/4 OF SECTION 6-21-13
- 3) STEVEN S. BROSEMER, L.S. 752, IN A LAND SURVEY REFERENCE REPORT DATED JANUARY 10, 1986, FOR JOB NUMBER 86134, SAID THAT **HE FOUND A 9" X 4" X 14" LIMESTONE** AT THE NORTH 1/4 CORNER OF SECTION 6-21-13 ON THE 4<sup>TH</sup> STANDARD PARALLEL. **HE PLACED 1/2" X 24" REBARS WITH HIS "LS 752" CAPS ON THE NORTH AND SOUTH SIDES OF THE STONE.**
  - 1) 32.15' TO A 1/2" REBAR IN THE ROAD
  - 2) 228.25 WEST TO A STONE AND REBAR [SW CORNER SECTION 31-20-13]
  - 3) IN THE CENTERLINE TRAVELED WAY EXTENDED OF THE ROAD TO THE SOUTH
  - 4) 2,399.36' SOUTH TO A 1/2" REBAR
- 4) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A LAND SURVEY REFERENCE REPORT DATED APRIL 28, 2006 FOR PROJECT NUMBER 06104-02, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A TRACT IN THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6 AND A TRACT IN FRACTIONAL SECTION 7 FOR KENT GREIDER, SAID THAT **HE FOUND THE 9" X 4" X 14" LIMESTONE** AT THE NORTH 1/4 CORNER OF SECTION 6-21-13 ON THE 4<sup>TH</sup> STANDARD PARALLEL FROM HIS EXISTING REFERENCE TIES ON FILE AT THE COUNTY ENGINEER'S OFFICE IN 1986.
  - 1) 1/2" REBARS WITH HIS "LS 752" CAPS ARE ON THE NORTH AND SOUTH SIDES OF THE STONE AND FLUSH WITH THE TOP CENTER OF THE STONE
  - 2) 32.15' SW TO A 1/2" REBAR IN THE GRAVEL ROAD AT THE MID POINT OF THE CURVE
  - 3) 228.25' WEST TO A STONE & REBAR [SW CORNER OF SECTION 31-20-13]
  - 4) 52.3' EAST TO A 40 D NAIL & WASHER IN A 14" WALNUT STUMP
  - 5) 27.0' WEST TO A 40 D NAIL & WASHER IN A LOCUST STUMP
  - 6) IN THE CENTERLINE TRAVELED WAY OF THE GRAVEL ROAD TO THE SOUTH EXTENDEDHIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
  - 1) 228.30' WEST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-20-12
  - 2) 1,324.09' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE NORTHEAST CORNER OF THE W1/2 OF THE NE1/4 OF FRACTIONAL SECTION 6-21-13
  - 3) 2,648.18' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF FRACTIONAL SECTION 6-21-13

HIS INFORMATION IS CONTINUED ON PAGE 2

- 4) 5,283.17' EAST ON THE 4<sup>TH</sup> STANDARD PARALLEL TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE FOUND AT THE NORTHEAST CORNER OF THE NW1/4 OF FRACTIONAL SECTION 5-21-13
- 5) 3,034.95' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF FRACTIONAL SECTION 6-21-13
- 6) 5,674.95' SOUTH TO THE 1/2" REBAR HE FOUND AT THE SOUTH 1/4 CORNER OF FRACTIONAL SECTION 6-21-13
- 7) 8,318.54' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE CENTER CORNER OF SECTION 7-21-13
- 8) 10,957.28' SOUTH TO THE 5/8" REBAR WITH A LYON COUNTY CAP HE SET FOR THE SOUTH 1/4 CORNER OF SECTION 7-21-13

NORTH QUARTER CORNER 06-21-13