

NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF SECTION 06, TOWNSHIP 21 SOUTH, RANGE 13 EAST

- 1) ROBERT MILLIKEN, COUNTY SURVEYOR FROM 1870 TO 1875 AND FROM 1882 TO 1883, IN SURVEY NUMBER 16, A PERMANENT SURVEY RECORDED IN SURVEY BOOK "B" ON PAGE 16 DATED MARCH 1-5, 1870 TO SUBDIVIDE THE NORTHEAST 1/4 OF SECTION 6-21-13, SAID THAT **HE SET A STONE** FOR THE PERMANENT NORTH 1/2/4 CORNER OF THE NORTHEAST 1/4 OF SECTION 6-21-13 ON THE 4TH STANDARD PARALLEL AND HALFWAY BETWEEN THE STONE THAT HE SET FOR THE NORTH 1/4 CORNER OF SECTION 6-21-13 AND THE STONE THAT HE FOUND AT THE NORTHEAST CORNER OF SECTION 6-21-13 ON THIS **PERMANENT SURVEY**.

- 2) STEVEN S. BROSEMER, L.S. 752, DEPUTY COUNTY SURVEYOR, IN A SECTION CORNER REPORT DATED APRIL 28, 2006 FOR PROJECT NUMBER 06104-02, SURVEY F06001 IN THE SURVEY FILE FOR TOWNSHIP 21-13 FOR A TRACT IN THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-21-13 AND A TRACT IN FRACTIONAL SECTION 7-21-13 FOR KENT GREIDER, SAID THAT HE DETERMINED THAT THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-21-13 FALLS IN A DEAD TREE ON LINE AND HALFWAY BETWEEN THE NORTH 1/4 CORNER AND THE THEORETICAL NORTHEAST CORNER OF FRACTIONAL SECTION 6-31-13. **HE SET A 1/2" X 24" REBAR WITH HIS "LS 752" CAP AS A WITNESS CORNER 3.0 FEET SOUTH OF THE TRUE POSITION FOR THE NORTH 1/16TH CORNER OF THE NORTHEAST 1/4 OF FRACTIONAL SECTION 6-21-13.**
 - 1) **3.0' NORTH TO THE TRUE POSITION**
HIS SURVEY DRAWING SHOWS THE FOLLOWING INFORMATION:
 - 1) 1,324.09' EAST ON THE 4TH STANDARD PARALLEL TO THE THEORETICAL POSITION FOR THE NORTHEAST CORNER OF FRACTIONAL SECTION 6-21-13
 - 2) 3,959.08' EAST ON THE 4TH STANDARD PARALLEL TO THE 1/2" REBAR WITH HIS "LS 752" CAP SET FOR THE NORTHEAST CORNER OF THE NW1/4 OF FRACTIONAL SECTION 5-21-13
 - 3) 1,324.09' WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE NORTHWEST CORNER OF THE NE1/4 OF FRACTIONAL SECTION 6-21-13
 - 4) 1,552.39' WEST ON THE 4TH STANDARD PARALLEL TO THE STONE HE FOUND AT THE SOUTHEAST CORNER OF SECTION 36-21-12
 - 5) 3,048.72' SOUTH TO THE 1/2" REBAR WITH HIS "LS 752" CAP HE SET FOR THE SOUTH 1/16TH CORNER OF THE NE1/4 OF FRACTIONAL SECTION 6-21-13

NORTH SIXTEENTH CORNER NORTHEAST CORNER 06-21-13